

What's in Main

Tobias Nipkow

October 25, 2022

Abstract

This document lists the main types, functions and syntax provided by theory *Main*. It is meant as a quick overview of what is available. For infix operators and their precedences see the final section. The sophisticated class structure is only hinted at. For details see <https://isabelle.in.tum.de/library/HOL/HOL>.

HOL

The basic logic: $x = y$, *True*, *False*, $\neg P$, $P \wedge Q$, $P \vee Q$, $P \longrightarrow Q$, $\forall x. P$, $\exists x. P$, $\exists!x. P$, *THE* $x. P$.

undefined :: 'a

default :: 'a

Syntax

$x \neq y$ \equiv $\neg (x = y)$ (\neq)

$P \longleftrightarrow Q$ \equiv $P = Q$

if x *then* y *else* z \equiv *If* x y z

let $x = e_1$ *in* e_2 \equiv *Let* e_1 ($\lambda x. e_2$)

Orderings

A collection of classes defining basic orderings: preorder, partial order, linear order, dense linear order and wellorder.

$(\leq) \quad :: 'a \Rightarrow 'a \Rightarrow bool \quad (<=)$
 $(<) \quad :: 'a \Rightarrow 'a \Rightarrow bool$
 $Least \quad :: ('a \Rightarrow bool) \Rightarrow 'a$
 $Greatest \quad :: ('a \Rightarrow bool) \Rightarrow 'a$
 $min \quad :: 'a \Rightarrow 'a \Rightarrow 'a$
 $max \quad :: 'a \Rightarrow 'a \Rightarrow 'a$
 $top \quad :: 'a$
 $bot \quad :: 'a$

Syntax

$x \geq y \quad \equiv \quad y \leq x \quad (>=)$
 $x > y \quad \equiv \quad y < x$
 $\forall x \leq y. P \quad \equiv \quad \forall x. x \leq y \longrightarrow P$
 $\exists x \leq y. P \quad \equiv \quad \exists x. x \leq y \wedge P$
 Similarly for $<$, \geq and $>$
 $LEAST x. P \quad \equiv \quad Least (\lambda x. P)$
 $GREATEST x. P \quad \equiv \quad Greatest (\lambda x. P)$

Lattices

Classes semilattice, lattice, distributive lattice and complete lattice (the latter in theory *HOL.Set*).

$inf \quad :: 'a \Rightarrow 'a \Rightarrow 'a$
 $sup \quad :: 'a \Rightarrow 'a \Rightarrow 'a$
 $Inf \quad :: 'a \text{ set} \Rightarrow 'a$
 $Sup \quad :: 'a \text{ set} \Rightarrow 'a$

Syntax

Available via **unbundle** *lattice_syntax*.

$x \sqsubseteq y \quad \equiv \quad x \leq y$
 $x \sqsubset y \quad \equiv \quad x < y$
 $x \sqcap y \quad \equiv \quad inf \ x \ y$
 $x \sqcup y \quad \equiv \quad sup \ x \ y$
 $\bigsqcap A \quad \equiv \quad Inf \ A$
 $\bigsqcup A \quad \equiv \quad Sup \ A$
 $\top \quad \equiv \quad top$
 $\perp \quad \equiv \quad bot$

Set

| | | |
|-----------|--|---------|
| $\{\}$ | $:: 'a \text{ set}$ | |
| $insert$ | $:: 'a \Rightarrow 'a \text{ set} \Rightarrow 'a \text{ set}$ | |
| $Collect$ | $:: ('a \Rightarrow bool) \Rightarrow 'a \text{ set}$ | |
| (\in) | $:: 'a \Rightarrow 'a \text{ set} \Rightarrow bool$ | $(:)$ |
| (\cup) | $:: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow 'a \text{ set}$ | (Un) |
| (\cap) | $:: 'a \text{ set} \Rightarrow 'a \text{ set} \Rightarrow 'a \text{ set}$ | (Int) |
| \bigcup | $:: 'a \text{ set set} \Rightarrow 'a \text{ set}$ | |
| \bigcap | $:: 'a \text{ set set} \Rightarrow 'a \text{ set}$ | |
| Pow | $:: 'a \text{ set} \Rightarrow 'a \text{ set set}$ | |
| $UNIV$ | $:: 'a \text{ set}$ | |
| $(')$ | $:: ('a \Rightarrow 'b) \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set}$ | |
| $Ball$ | $:: 'a \text{ set} \Rightarrow ('a \Rightarrow bool) \Rightarrow bool$ | |
| Bex | $:: 'a \text{ set} \Rightarrow ('a \Rightarrow bool) \Rightarrow bool$ | |

Syntax

| | | |
|-------------------------------|---|---------|
| $\{a_1, \dots, a_n\}$ | $\equiv insert\ a_1\ (\dots\ (insert\ a_n\ \{\})\dots)$ | |
| $a \notin A$ | $\equiv \neg(x \in A)$ | |
| $A \subseteq B$ | $\equiv A \leq B$ | |
| $A \subset B$ | $\equiv A < B$ | |
| $A \supseteq B$ | $\equiv B \leq A$ | |
| $A \supset B$ | $\equiv B < A$ | |
| $\{x. P\}$ | $\equiv Collect\ (\lambda x. P)$ | |
| $\{t \mid x_1 \dots x_n. P\}$ | $\equiv \{v. \exists x_1 \dots x_n. v = t \wedge P\}$ | |
| $\bigcup_{x \in I}. A$ | $\equiv \bigcup ((\lambda x. A) ' I)$ | (UN) |
| $\bigcup x. A$ | $\equiv \bigcup ((\lambda x. A) ' UNIV)$ | |
| $\bigcap_{x \in I}. A$ | $\equiv \bigcap ((\lambda x. A) ' I)$ | (INT) |
| $\bigcap x. A$ | $\equiv \bigcap ((\lambda x. A) ' UNIV)$ | |
| $\forall x \in A. P$ | $\equiv Ball\ A\ (\lambda x. P)$ | |
| $\exists x \in A. P$ | $\equiv Bex\ A\ (\lambda x. P)$ | |
| $range\ f$ | $\equiv f ' UNIV$ | |

Fun

| | | |
|-----------------------|--|-----|
| <i>id</i> | :: 'a ⇒ 'a | |
| (○) | :: ('a ⇒ 'b) ⇒ ('c ⇒ 'a) ⇒ 'c ⇒ 'b | (○) |
| <i>inj_on</i> | :: ('a ⇒ 'b) ⇒ 'a set ⇒ bool | |
| <i>inj</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>surj</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>bij</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>bij_betw</i> | :: ('a ⇒ 'b) ⇒ 'a set ⇒ 'b set ⇒ bool | |
| <i>monotone_on</i> | :: 'a set ⇒ ('a ⇒ 'a ⇒ bool) ⇒ ('b ⇒ 'b ⇒ bool) ⇒ ('a ⇒ 'b) ⇒ bool | |
| <i>monotone</i> | :: ('a ⇒ 'a ⇒ bool) ⇒ ('b ⇒ 'b ⇒ bool) ⇒ ('a ⇒ 'b) ⇒ bool | |
| <i>mono_on</i> | :: 'a set ⇒ ('a ⇒ 'b) ⇒ bool | |
| <i>mono</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>strict_mono_on</i> | :: 'a set ⇒ ('a ⇒ 'b) ⇒ bool | |
| <i>strict_mono</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>antimono</i> | :: ('a ⇒ 'b) ⇒ bool | |
| <i>fun_upd</i> | :: ('a ⇒ 'b) ⇒ 'a ⇒ 'b ⇒ 'a ⇒ 'b | |

Syntax

| | | |
|--------------------------------|---|--------------------------------|
| $f(x := y)$ | ≡ | $fun_upd\ f\ x\ y$ |
| $f(x_1:=y_1, \dots, x_n:=y_n)$ | ≡ | $f(x_1:=y_1) \dots (x_n:=y_n)$ |

Hilbert__Choice

Hilbert's selection (ε) operator: *SOME* x . P .

$inv_into :: 'a\ set \Rightarrow ('a \Rightarrow 'b) \Rightarrow 'b \Rightarrow 'a$

Syntax

$inv \equiv inv_into\ UNIV$

Fixed Points

Theory: *HOL.Inductive*.

Least and greatest fixed points in a complete lattice 'a:

$lfp :: ('a \Rightarrow 'a) \Rightarrow 'a$

$gfp :: ('a \Rightarrow 'a) \Rightarrow 'a$

Note that in particular sets ($'a \Rightarrow bool$) are complete lattices.

Sum_Type

Type constructor $+$.

Inl $:: 'a \Rightarrow 'a + 'b$

Inr $:: 'a \Rightarrow 'b + 'a$

$(<+>)$ $:: 'a \text{ set} \Rightarrow 'b \text{ set} \Rightarrow ('a + 'b) \text{ set}$

Product_Type

Types $unit$ and \times .

$()$ $:: unit$

$Pair$ $:: 'a \Rightarrow 'b \Rightarrow 'a \times 'b$

fst $:: 'a \times 'b \Rightarrow 'a$

snd $:: 'a \times 'b \Rightarrow 'b$

$case_prod$ $:: ('a \Rightarrow 'b \Rightarrow 'c) \Rightarrow 'a \times 'b \Rightarrow 'c$

$curry$ $:: ('a \times 'b \Rightarrow 'c) \Rightarrow 'a \Rightarrow 'b \Rightarrow 'c$

$Sigma$ $:: 'a \text{ set} \Rightarrow ('a \Rightarrow 'b \text{ set}) \Rightarrow ('a \times 'b) \text{ set}$

Syntax

(a, b) $\equiv Pair\ a\ b$

$\lambda(x, y). t$ $\equiv case_prod\ (\lambda x\ y. t)$

$A \times B$ $\equiv Sigma\ A\ (\lambda_. B)$

Pairs may be nested. Nesting to the right is printed as a tuple, e.g. (a, b, c) is really $(a, (b, c))$. Pattern matching with pairs and tuples extends to all binders, e.g. $\forall (x, y) \in A. P$, $\{(x, y). P\}$, etc.

Relation

$converse$ $:: ('a \times 'b) \text{ set} \Rightarrow ('b \times 'a) \text{ set}$

(O) $:: ('a \times 'b) \text{ set} \Rightarrow ('b \times 'c) \text{ set} \Rightarrow ('a \times 'c) \text{ set}$

$(“)$ $:: ('a \times 'b) \text{ set} \Rightarrow 'a \text{ set} \Rightarrow 'b \text{ set}$

inv_image $:: ('a \times 'a) \text{ set} \Rightarrow ('b \Rightarrow 'a) \Rightarrow ('b \times 'b) \text{ set}$

Id_on $:: 'a \text{ set} \Rightarrow ('a \times 'a) \text{ set}$

Id $:: ('a \times 'a) \text{ set}$

$Domain$ $:: ('a \times 'b) \text{ set} \Rightarrow 'a \text{ set}$

$Range$ $:: ('a \times 'b) \text{ set} \Rightarrow 'b \text{ set}$

Field :: ('a × 'a) set ⇒ 'a set
refl_on :: 'a set ⇒ ('a × 'a) set ⇒ bool
refl :: ('a × 'a) set ⇒ bool
sym :: ('a × 'a) set ⇒ bool
antisym :: ('a × 'a) set ⇒ bool
trans :: ('a × 'a) set ⇒ bool
irrefl :: ('a × 'a) set ⇒ bool
total_on :: 'a set ⇒ ('a × 'a) set ⇒ bool
total :: ('a × 'a) set ⇒ bool

Syntax

$r^{-1} \equiv \text{converse } r \quad (\hat{-1})$

Type synonym $'a \text{ rel} = ('a \times 'a) \text{ set}$

Equiv_Relations

equiv :: 'a set ⇒ ('a × 'a) set ⇒ bool
(//) :: 'a set ⇒ ('a × 'a) set ⇒ 'a set set
congruent :: ('a × 'a) set ⇒ ('a ⇒ 'b) ⇒ bool
congruent2 :: ('a × 'a) set ⇒ ('b × 'b) set ⇒ ('a ⇒ 'b ⇒ 'c) ⇒ bool

Syntax

f respects r ≡ *congruent r f*
f respects2 r ≡ *congruent2 r r f*

Transitive_Closure

rtrancl :: ('a × 'a) set ⇒ ('a × 'a) set
trancl :: ('a × 'a) set ⇒ ('a × 'a) set
reflcl :: ('a × 'a) set ⇒ ('a × 'a) set
acyclic :: ('a × 'a) set ⇒ bool
($\widetilde{\sim}$) :: ('a × 'a) set ⇒ nat ⇒ ('a × 'a) set

Syntax

$r^* \equiv rtrancl\ r \quad (\hat{~}^*)$
 $r^+ \equiv trancl\ r \quad (\hat{~}^+)$
 $r^- \equiv reflcl\ r \quad (\hat{~}^-)$

Algebra

Theories *HOL.Groups*, *HOL.Rings*, *HOL.Fields* and *HOL.Divides* define a large collection of classes describing common algebraic structures from semi-groups up to fields. Everything is done in terms of overloaded operators:

$0 \quad \quad \quad :: 'a$
 $1 \quad \quad \quad :: 'a$
 $(+)$ $:: 'a \Rightarrow 'a \Rightarrow 'a$
 $(-)$ $:: 'a \Rightarrow 'a \Rightarrow 'a$
uminus $:: 'a \Rightarrow 'a \quad \quad \quad (-)$
 $(*)$ $:: 'a \Rightarrow 'a \Rightarrow 'a$
inverse $:: 'a \Rightarrow 'a$
 (div) $:: 'a \Rightarrow 'a \Rightarrow 'a$
abs $:: 'a \Rightarrow 'a$
sgn $:: 'a \Rightarrow 'a$
 (dvd) $:: 'a \Rightarrow 'a \Rightarrow bool$
 (div) $:: 'a \Rightarrow 'a \Rightarrow 'a$
 (mod) $:: 'a \Rightarrow 'a \Rightarrow 'a$

Syntax

$|x| \equiv abs\ x$

Nat

datatype *nat* = 0 | *Suc nat*

$(+)$ $(-)$ $(*)$ $(\hat{~})$ (div) (mod) (dvd)
 (\leq) $(<)$ *min* *max* *Min* *Max*
of_nat $:: nat \Rightarrow 'a$
 $(\hat{~})$ $:: ('a \Rightarrow 'a) \Rightarrow nat \Rightarrow 'a \Rightarrow 'a$

Int

Type *int*

(+) (-) *uminus* (*) (\wedge) (*div*) (*mod*) (*dvd*)
(\leq) (<) *min* *max* *Min* *Max*
abs *sgn*

nat :: *int* \Rightarrow *nat*

of_int :: *int* \Rightarrow 'a

\mathbb{Z} :: 'a *set* (Ints)

Syntax

int \equiv *of_nat*

Finite_Set

finite :: 'a *set* \Rightarrow *bool*

card :: 'a *set* \Rightarrow *nat*

Finite_Set.fold :: ('a \Rightarrow 'b \Rightarrow 'b) \Rightarrow 'b \Rightarrow 'a *set* \Rightarrow 'b

Lattices_Big

Min :: 'a *set* \Rightarrow 'a

Max :: 'a *set* \Rightarrow 'a

arg_min :: ('a \Rightarrow 'b) \Rightarrow ('a \Rightarrow *bool*) \Rightarrow 'a

is_arg_min :: ('a \Rightarrow 'b) \Rightarrow ('a \Rightarrow *bool*) \Rightarrow 'a \Rightarrow *bool*

arg_max :: ('a \Rightarrow 'b) \Rightarrow ('a \Rightarrow *bool*) \Rightarrow 'a

is_arg_max :: ('a \Rightarrow 'b) \Rightarrow ('a \Rightarrow *bool*) \Rightarrow 'a \Rightarrow *bool*

Syntax

ARG_MIN *f x. P* \equiv *arg_min* *f* ($\lambda x. P$)

ARG_MAX *f x. P* \equiv *arg_max* *f* ($\lambda x. P$)

Groups_Big

sum :: ('a \Rightarrow 'b) \Rightarrow 'a *set* \Rightarrow 'b

prod :: ('a \Rightarrow 'b) \Rightarrow 'a *set* \Rightarrow 'b

Syntax

$$\begin{aligned}\sum A &\equiv \text{sum } (\lambda x. x) A \quad (\text{SUM}) \\ \sum_{x \in A}. t &\equiv \text{sum } (\lambda x. t) A \\ \sum x | P. t &\equiv \sum x | P. t \\ \text{Similarly for } \prod &\text{ instead of } \sum \quad (\text{PROD})\end{aligned}$$

Wellfounded

$$\begin{aligned}\text{wf} &:: ('a \times 'a) \text{ set} \Rightarrow \text{bool} \\ \text{Wellfounded.acc} &:: ('a \times 'a) \text{ set} \Rightarrow 'a \text{ set} \\ \text{measure} &:: ('a \Rightarrow \text{nat}) \Rightarrow ('a \times 'a) \text{ set} \\ (<*\text{lex}* >) &:: ('a \times 'a) \text{ set} \Rightarrow ('b \times 'b) \text{ set} \Rightarrow (('a \times 'b) \times 'a \times 'b) \text{ set} \\ (<*\text{mlex}* >) &:: ('a \Rightarrow \text{nat}) \Rightarrow ('a \times 'a) \text{ set} \Rightarrow ('a \times 'a) \text{ set} \\ \text{less_than} &:: (\text{nat} \times \text{nat}) \text{ set} \\ \text{pred_nat} &:: (\text{nat} \times \text{nat}) \text{ set}\end{aligned}$$

Set_Interval

$$\begin{aligned}\text{lessThan} &:: 'a \Rightarrow 'a \text{ set} \\ \text{atMost} &:: 'a \Rightarrow 'a \text{ set} \\ \text{greaterThan} &:: 'a \Rightarrow 'a \text{ set} \\ \text{atLeast} &:: 'a \Rightarrow 'a \text{ set} \\ \text{greaterThanLessThan} &:: 'a \Rightarrow 'a \Rightarrow 'a \text{ set} \\ \text{atLeastLessThan} &:: 'a \Rightarrow 'a \Rightarrow 'a \text{ set} \\ \text{greaterThanAtMost} &:: 'a \Rightarrow 'a \Rightarrow 'a \text{ set} \\ \text{atLeastAtMost} &:: 'a \Rightarrow 'a \Rightarrow 'a \text{ set}\end{aligned}$$

Syntax

| | | |
|-------------------------|----------|-------------------------------|
| $\{..<y\}$ | \equiv | $lessThan\ y$ |
| $\{..y\}$ | \equiv | $atMost\ y$ |
| $\{x<..\}$ | \equiv | $greaterThan\ x$ |
| $\{x..\}$ | \equiv | $atLeast\ x$ |
| $\{x<..<y\}$ | \equiv | $greaterThanLessThan\ x\ y$ |
| $\{x..<y\}$ | \equiv | $atLeastLessThan\ x\ y$ |
| $\{x<..y\}$ | \equiv | $greaterThanAtMost\ x\ y$ |
| $\{x..y\}$ | \equiv | $atLeastAtMost\ x\ y$ |
| $\bigcup_{i \leq n}. A$ | \equiv | $\bigcup_{i \in \{..n\}}. A$ |
| $\bigcup_{i < n}. A$ | \equiv | $\bigcup_{i \in \{..<n\}}. A$ |

Similarly for \bigcap instead of \bigcup

| | | |
|---------------------|----------|----------------------------------|
| $\sum x = a..b. t$ | \equiv | $sum\ (\lambda x. t)\ \{a..b\}$ |
| $\sum x = a..<b. t$ | \equiv | $sum\ (\lambda x. t)\ \{a..<b\}$ |
| $\sum x \leq b. t$ | \equiv | $sum\ (\lambda x. t)\ \{..b\}$ |
| $\sum x < b. t$ | \equiv | $sum\ (\lambda x. t)\ \{..<b\}$ |

Similarly for \prod instead of \sum

Power

$(\wedge) :: 'a \Rightarrow nat \Rightarrow 'a$

Option

datatype $'a\ option = None \mid Some\ 'a$

$the :: 'a\ option \Rightarrow 'a$

$map_option :: ('a \Rightarrow 'b) \Rightarrow 'a\ option \Rightarrow 'b\ option$

$set_option :: 'a\ option \Rightarrow 'a\ set$

$Option.bind :: 'a\ option \Rightarrow ('a \Rightarrow 'b\ option) \Rightarrow 'b\ option$

List

datatype $'a\ list = [] \mid (\#)\ 'a\ ('a\ list)$

$(@) :: 'a\ list \Rightarrow 'a\ list \Rightarrow 'a\ list$

butlast :: 'a list \Rightarrow 'a list
concat :: 'a list list \Rightarrow 'a list
distinct :: 'a list \Rightarrow bool
drop :: nat \Rightarrow 'a list \Rightarrow 'a list
dropWhile :: ('a \Rightarrow bool) \Rightarrow 'a list \Rightarrow 'a list
filter :: ('a \Rightarrow bool) \Rightarrow 'a list \Rightarrow 'a list
find :: ('a \Rightarrow bool) \Rightarrow 'a list \Rightarrow 'a option
fold :: ('a \Rightarrow 'b \Rightarrow 'b) \Rightarrow 'a list \Rightarrow 'b \Rightarrow 'b
foldr :: ('a \Rightarrow 'b \Rightarrow 'b) \Rightarrow 'a list \Rightarrow 'b \Rightarrow 'b
foldl :: ('a \Rightarrow 'b \Rightarrow 'a) \Rightarrow 'a \Rightarrow 'b list \Rightarrow 'a
hd :: 'a list \Rightarrow 'a
last :: 'a list \Rightarrow 'a
length :: 'a list \Rightarrow nat
lenlex :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set
lex :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set
lexn :: ('a \times 'a) set \Rightarrow nat \Rightarrow ('a list \times 'a list) set
lexord :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set
listrel :: ('a \times 'b) set \Rightarrow ('a list \times 'b list) set
listrel1 :: ('a \times 'a) set \Rightarrow ('a list \times 'a list) set
lists :: 'a set \Rightarrow 'a list set
listset :: 'a set list \Rightarrow 'a list set
sum_list :: 'a list \Rightarrow 'a
prod_list :: 'a list \Rightarrow 'a
list_all2 :: ('a \Rightarrow 'b \Rightarrow bool) \Rightarrow 'a list \Rightarrow 'b list \Rightarrow bool
list_update :: 'a list \Rightarrow nat \Rightarrow 'a \Rightarrow 'a list
map :: ('a \Rightarrow 'b) \Rightarrow 'a list \Rightarrow 'b list
measures :: ('a \Rightarrow nat) list \Rightarrow ('a \times 'a) set
(!) :: 'a list \Rightarrow nat \Rightarrow 'a
nths :: 'a list \Rightarrow nat set \Rightarrow 'a list
remdups :: 'a list \Rightarrow 'a list
removeAll :: 'a \Rightarrow 'a list \Rightarrow 'a list
remove1 :: 'a \Rightarrow 'a list \Rightarrow 'a list
replicate :: nat \Rightarrow 'a \Rightarrow 'a list
rev :: 'a list \Rightarrow 'a list
rotate :: nat \Rightarrow 'a list \Rightarrow 'a list
rotate1 :: 'a list \Rightarrow 'a list
set :: 'a list \Rightarrow 'a set
shuffles :: 'a list \Rightarrow 'a list \Rightarrow 'a list set
sort :: 'a list \Rightarrow 'a list

sorted :: 'a list ⇒ bool
sorted_wrt :: ('a ⇒ 'a ⇒ bool) ⇒ 'a list ⇒ bool
splICE :: 'a list ⇒ 'a list ⇒ 'a list
take :: nat ⇒ 'a list ⇒ 'a list
takeWhile :: ('a ⇒ bool) ⇒ 'a list ⇒ 'a list
tl :: 'a list ⇒ 'a list
upt :: nat ⇒ nat ⇒ nat list
upto :: int ⇒ int ⇒ int list
zip :: 'a list ⇒ 'b list ⇒ ('a × 'b) list

Syntax

$[x_1, \dots, x_n]$ ≡ $x_1 \# \dots \# x_n \# []$
 $[m..<n]$ ≡ *upt* m n
 $[i..j]$ ≡ *upto* i j
 $xs[n := x]$ ≡ *list_update* xs n x
 $\sum x \leftarrow xs. e$ ≡ *listsum* (*map* ($\lambda x. e$) xs)

Filter input syntax $[pat \leftarrow e. b]$, where *pat* is a tuple pattern, which stands for *filter* ($\lambda pat. b$) e .

List comprehension input syntax: $[e. q_1, \dots, q_n]$ where each qualifier q_i is either a generator $pat \leftarrow e$ or a guard, i.e. boolean expression.

Map

Maps model partial functions and are often used as finite tables. However, the domain of a map may be infinite.

Map.empty :: 'a ⇒ 'b option
 $(++)$:: ('a ⇒ 'b option) ⇒ ('a ⇒ 'b option) ⇒ 'a ⇒ 'b option
 (\circ_m) :: ('a ⇒ 'b option) ⇒ ('c ⇒ 'a option) ⇒ 'c ⇒ 'b option
 $(|')$:: ('a ⇒ 'b option) ⇒ 'a set ⇒ 'a ⇒ 'b option
dom :: ('a ⇒ 'b option) ⇒ 'a set
ran :: ('a ⇒ 'b option) ⇒ 'b set
 (\subseteq_m) :: ('a ⇒ 'b option) ⇒ ('a ⇒ 'b option) ⇒ bool
map_of :: ('a × 'b) list ⇒ 'a ⇒ 'b option
map_upds :: ('a ⇒ 'b option) ⇒ 'a list ⇒ 'b list ⇒ 'a ⇒ 'b option

Syntax

| | | |
|--|----------|--|
| $Map.empty$ | \equiv | $\lambda_ . None$ |
| $m(x \mapsto y)$ | \equiv | $m(x := Some\ y)$ |
| $m(x_1 \mapsto y_1, \dots, x_n \mapsto y_n)$ | \equiv | $m(x_1 \mapsto y_1) \dots (x_n \mapsto y_n)$ |
| $[x_1 \mapsto y_1, \dots, x_n \mapsto y_n]$ | \equiv | $Map.empty(x_1 \mapsto y_1, \dots, x_n \mapsto y_n)$ |
| $m(xs \ [\mapsto] \ ys)$ | \equiv | $map_upds\ m\ xs\ ys$ |

Infix operators in Main

| | Operator | precedence | associativity |
|-------------------------|--|------------|---------------|
| Meta-logic | \implies | 1 | right |
| | \equiv | 2 | |
| Logic | \wedge | 35 | right |
| | \vee | 30 | right |
| | $\longrightarrow, \longleftrightarrow$ | 25 | right |
| | $=, \neq$ | 50 | left |
| Orderings | $\leq, <, \geq, >$ | 50 | |
| Sets | $\subseteq, \subset, \supseteq, \supset$ | 50 | |
| | \in, \notin | 50 | |
| | \cap | 70 | left |
| | \cup | 65 | left |
| Functions and Relations | \circ | 55 | left |
| | $'$ | 90 | right |
| | O | 75 | right |
| | $“$ | 90 | right |
| | \rightsquigarrow | 80 | right |
| Numbers | $+, -$ | 65 | left |
| | $*, /$ | 70 | left |
| | div, mod | 70 | left |
| | \wedge | 80 | right |
| | dvd | 50 | |
| Lists | $\#, @$ | 65 | right |
| | $!$ | 100 | left |