IMP — A `WHILE`-language and two semantics

Heiko Loetzbeyer and Robert Sandner

January 30, 2011

Abstract

The formalization of the denotational and operational semantics of a simple while-language together with an equivalence proof between the two semantics. The whole development essentially formalizes/transcribes chapters 2 and 5 of [1]. A much extended version of this development is found in HOL/IMP of the Isabelle distribution.

Contents

1 Arithmetic expressions, boolean expressions, commands **1**
- 1.1 Arithmetic expressions . . . 1
- 1.2 Boolean expressions . . . 2
- 1.3 Commands . . . 3
- 1.4 Misc lemmas . . . 4

2 Denotational semantics of expressions and commands **4**
- 2.1 Definitions . . . 4
- 2.2 Misc lemmas . . . 5

3 Equivalence **5**
- 3.1 Main theorem . . . 7

1 Arithmetic expressions, boolean expressions, commands

theory *Com* **imports** *Main* **begin**

1.1 Arithmetic expressions

consts
```
  loc :: i
  aexp :: i
```

datatype ⊆ *"univ(loc ∪ (nat -> nat) ∪ ((nat × nat) -> nat))"*
```
  aexp = N ("n ∈ nat")
```

```
      | X ("x ∈ loc")
      | Op1 ("f ∈ nat -> nat", "a ∈ aexp")
      | Op2 ("f ∈ (nat × nat) -> nat", "a0 ∈ aexp", "a1 ∈ aexp")


consts evala :: i

abbreviation
  evala_syntax :: "[i, i] => o"    (infixl "-a->" 50)
  where "p -a-> n == <p,n> ∈ evala"

inductive
  domains "evala" ⊆ "(aexp × (loc -> nat)) × nat"
  intros
    N:   "[| n ∈ nat;  sigma ∈ loc->nat |] ==> <N(n),sigma> -a-> n"
    X:   "[| x ∈ loc;  sigma ∈ loc->nat |] ==> <X(x),sigma> -a-> sigma`x"
    Op1: "[| <e,sigma> -a-> n; f ∈ nat -> nat |] ==> <Op1(f,e),sigma> -a-> f`n"
    Op2: "[| <e0,sigma> -a-> n0;  <e1,sigma>  -a-> n1; f ∈ (nat×nat) -> nat |]
          ==> <Op2(f,e0,e1),sigma> -a-> f`<n0,n1>"
  type_intros aexp.intros apply_funtype
```

1.2 Boolean expressions

```
consts bexp :: i

datatype ⊆ "univ(aexp ∪ ((nat × nat)->bool))"
  bexp = true
       | false
       | ROp  ("f ∈ (nat × nat)->bool", "a0 ∈ aexp", "a1 ∈ aexp")
       | noti ("b ∈ bexp")
       | andi ("b0 ∈ bexp", "b1 ∈ bexp")      (infixl "andi" 60)
       | ori  ("b0 ∈ bexp", "b1 ∈ bexp")      (infixl "ori" 60)


consts evalb :: i

abbreviation
  evalb_syntax :: "[i,i] => o"    (infixl "-b->" 50)
  where "p -b-> b == <p,b> ∈ evalb"

inductive
  domains "evalb" ⊆ "(bexp × (loc -> nat)) × bool"
  intros
    true:  "[| sigma ∈ loc -> nat |] ==> <true,sigma> -b-> 1"
    false: "[| sigma ∈ loc -> nat |] ==> <false,sigma> -b-> 0"
    ROp:   "[| <a0,sigma> -a-> n0; <a1,sigma> -a-> n1; f ∈ (nat*nat)->bool |]
           ==> <ROp(f,a0,a1),sigma> -b-> f`<n0,n1> "
    noti:  "[| <b,sigma> -b-> w |] ==> <noti(b),sigma> -b-> not(w)"
    andi:  "[| <b0,sigma> -b-> w0; <b1,sigma> -b-> w1 |]
          ==> <b0 andi b1,sigma> -b-> (w0 and w1)"
```

```
    ori:   "[| <b0,sigma> -b-> w0; <b1,sigma> -b-> w1 |]
            ==> <b0 ori b1,sigma> -b-> (w0 or w1)"
  type_intros  bexp.intros
               apply_funtype and_type or_type bool_1I bool_0I not_type
  type_elims   evala.dom_subset [THEN subsetD, elim_format]
```

1.3 Commands

```
consts com :: i
datatype com =
    skip                                    ("skip" [])
  | assignment ("x ∈ loc", "a ∈ aexp")        (infixl ":=" 60)
  | semicolon ("c0 ∈ com", "c1 ∈ com")        ("_; _"  [60, 60] 10)
  | while ("b ∈ bexp", "c ∈ com")             ("while _ do _"  60)
  | "if" ("b ∈ bexp", "c0 ∈ com", "c1 ∈ com")    ("if _ then _ else _" 60)


consts evalc :: i

abbreviation
  evalc_syntax :: "[i, i] => o"    (infixl "-c->" 50)
  where "p -c-> s == <p,s> ∈ evalc"

inductive
  domains "evalc" ⊆ "(com × (loc -> nat)) × (loc -> nat)"
  intros
    skip:    "[| sigma ∈ loc -> nat |] ==> <skip,sigma> -c-> sigma"

    assign:  "[| m ∈ nat; x ∈ loc; <a,sigma> -a-> m |]
              ==> <x := a,sigma> -c-> sigma(x:=m)"

    semi:    "[| <c0,sigma> -c-> sigma2; <c1,sigma2> -c-> sigma1 |]
              ==> <c0; c1, sigma> -c-> sigma1"

    if1:     "[| b ∈ bexp; c1 ∈ com; sigma ∈ loc->nat;
                <b,sigma> -b-> 1; <c0,sigma> -c-> sigma1 |]
             ==> <if b then c0 else c1, sigma> -c-> sigma1"

    if0:     "[| b ∈ bexp; c0 ∈ com; sigma ∈ loc->nat;
                <b,sigma> -b-> 0; <c1,sigma> -c-> sigma1 |]
              ==> <if b then c0 else c1, sigma> -c-> sigma1"

    while0:   "[| c ∈ com; <b, sigma> -b-> 0 |]
               ==> <while b do c,sigma> -c-> sigma"

    while1:   "[| c ∈ com; <b,sigma> -b-> 1; <c,sigma> -c-> sigma2;
                  <while b do c, sigma2> -c-> sigma1 |]
               ==> <while b do c, sigma> -c-> sigma1"

  type_intros  com.intros update_type
```

type_elims *evala.dom_subset [THEN subsetD, elim_format]*
evalb.dom_subset [THEN subsetD, elim_format]

1.4 Misc lemmas

lemmas *evala_1 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]*
and *evala_2 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]*
and *evala_3 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD2]*

lemmas *evalb_1 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]*
and *evalb_2 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]*
and *evalb_3 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD2]*

lemmas *evalc_1 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]*
and *evalc_2 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]*
and *evalc_3 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD2]*

inductive_cases
evala_N_E [elim!]: "<N(n),sigma> -a-> i"
and *evala_X_E [elim!]: "<X(x),sigma> -a-> i"*
and *evala_Op1_E [elim!]: "<Op1(f,e),sigma> -a-> i"*
and *evala_Op2_E [elim!]: "<Op2(f,a1,a2),sigma> -a-> i"*

end

2 Denotational semantics of expressions and commands

theory *Denotation* **imports** *Com* **begin**

2.1 Definitions

consts
A :: "i => i => i"
B :: "i => i => i"
C :: "i => i"

definition
Gamma :: "[i,i,i] => i" ("Γ") **where**
"Γ(b,cden) ==
(λphi. {io ∈ (phi O cden). B(b,fst(io))=1} ∪
{io ∈ id(loc->nat). B(b,fst(io))=0})"

primrec
"A(N(n), sigma) = n"
"A(X(x), sigma) = sigma`x"
"A(Op1(f,a), sigma) = f`A(a,sigma)"
"A(Op2(f,a0,a1), sigma) = f`<A(a0,sigma),A(a1,sigma)>"

```
primrec
  "B(true, sigma) = 1"
  "B(false, sigma) = 0"
  "B(ROp(f,a0,a1), sigma) = f`<A(a0,sigma),A(a1,sigma)>"
  "B(noti(b), sigma) = not(B(b,sigma))"
  "B(b0 andi b1, sigma) = B(b0,sigma) and B(b1,sigma)"
  "B(b0 ori b1, sigma) = B(b0,sigma) or B(b1,sigma)"

primrec
  "C(skip) = id(loc->nat)"
  "C(x := a) =
    {io ∈ (loc->nat) × (loc->nat). snd(io) = fst(io)(x := A(a,fst(io)))}"
  "C(c0; c1) = C(c1) O C(c0)"
  "C(if b then c0 else c1) =
    {io ∈ C(c0). B(b,fst(io)) = 1} ∪ {io ∈ C(c1). B(b,fst(io)) = 0}"
  "C(while b do c) = lfp((loc->nat) × (loc->nat), Γ(b,C(c)))"
```

2.2 Misc lemmas

```
lemma A_type [TC]: "[|a ∈ aexp; sigma ∈ loc->nat|] ==> A(a,sigma) ∈ nat"
  by (erule aexp.induct) simp_all

lemma B_type [TC]: "[|b ∈ bexp; sigma ∈ loc->nat|] ==> B(b,sigma) ∈ bool"
by (erule bexp.induct, simp_all)

lemma C_subset: "c ∈ com ==> C(c) ⊆ (loc->nat) × (loc->nat)"
  apply (erule com.induct)
      apply simp_all
      apply (blast dest: lfp_subset [THEN subsetD])+
  done

lemma C_type_D [dest]:
    "[| <x,y> ∈ C(c); c ∈ com |] ==> x ∈ loc->nat & y ∈ loc->nat"
  by (blast dest: C_subset [THEN subsetD])

lemma C_type_fst [dest]: "[| x ∈ C(c); c ∈ com |] ==> fst(x) ∈ loc->nat"
  by (auto dest!: C_subset [THEN subsetD])

lemma Gamma_bnd_mono:
  "cden ⊆ (loc->nat) × (loc->nat)
    ==> bnd_mono ((loc->nat) × (loc->nat), Γ(b,cden))"
  by (unfold bnd_mono_def Gamma_def) blast

end
```

3 Equivalence

```
theory Equiv imports Denotation Com begin
```

```
lemma aexp_iff [rule_format]:
  "[| a ∈ aexp; sigma: loc -> nat |]
    ==> ALL n. <a,sigma> -a-> n <-> A(a,sigma) = n"
  apply (erule aexp.induct)
     apply (force intro!: evala.intros)+
  done

declare aexp_iff [THEN iffD1, simp]
        aexp_iff [THEN iffD2, intro!]

inductive_cases [elim!]:
  "<true,sigma> -b-> x"
  "<false,sigma> -b-> x"
  "<ROp(f,a0,a1),sigma> -b-> x"
  "<noti(b),sigma> -b-> x"
  "<b0 andi b1,sigma> -b-> x"
  "<b0 ori b1,sigma> -b-> x"


lemma bexp_iff [rule_format]:
  "[| b ∈ bexp; sigma: loc -> nat |]
    ==> ALL w. <b,sigma> -b-> w <-> B(b,sigma) = w"
  apply (erule bexp.induct)
  apply (auto intro!: evalb.intros)
  done

declare bexp_iff [THEN iffD1, simp]
        bexp_iff [THEN iffD2, intro!]

lemma com1: "<c,sigma> -c-> sigma' ==> <sigma,sigma'> ∈ C(c)"
  apply (erule evalc.induct)
        apply (simp_all (no_asm_simp))

assign

     apply (simp add: update_type)

comp

    apply fast

while

   apply (erule Gamma_bnd_mono [THEN lfp_unfold, THEN ssubst, OF C_subset])
   apply (simp add: Gamma_def)
```

recursive case of `while`

```
  apply (erule Gamma_bnd_mono [THEN lfp_unfold, THEN ssubst, OF C_subset])
  apply (auto simp add: Gamma_def)
  done
```

```
declare B_type [intro!] A_type [intro!]
declare evalc.intros [intro]


lemma com2 [rule_format]: "c ∈ com ==> ∀x ∈ C(c). <c,fst(x)> -c-> snd(x)"
  apply (erule com.induct)

skip

     apply force

assign

    apply force

comp

   apply force

while

   apply safe
   apply simp_all
   apply (frule Gamma_bnd_mono [OF C_subset], erule Fixedpt.induct, assumption)
   apply (unfold Gamma_def)
   apply force

if

  apply auto
  done
```

3.1 Main theorem

```
theorem com_equivalence:
    "c ∈ com ==> C(c) = {io ∈ (loc->nat) × (loc->nat). <c,fst(io)> -c-> snd(io)}"
  by (force intro: C_subset [THEN subsetD] elim: com2 dest: com1)

end
```

References

[1] Glynn Winskel. *The Formal Semantics of Programming Languages*. 1993.