Examples of Inductive and Coinductive Definitions in HOL

Stefan Berghofer
Tobias Nipkow
Lawrence C Paulson
Markus Wenzel

February 20, 2021

Abstract

This is a collection of small examples to demonstrate Isabelle/HOL's (co)inductive definitions package. Large examples appear on many other sessions, such as Lambda, IMP, and Auth.

Contents

1 Common patterns of induction **4**
1.1 Variations on statement structure 4
1.1.1 Local facts and parameters 4
1.1.2 Local definitions 4
1.1.3 Simple simultaneous goals 5
1.1.4 Compound simultaneous goals 6
1.2 Multiple rules 7
1.3 Inductive predicates 9

2 Nested datatypes **11**
2.1 Terms and substitution 11
2.2 Alternative induction 12

3 Defining an Initial Algebra by Quotienting a Free Algebra **12**
3.1 Defining the Free Algebra 12
3.2 Some Functions on the Free Algebra 13
3.2.1 The Set of Nonces 13
3.2.2 The Left Projection 13
3.2.3 The Right Projection 14
3.2.4 The Discriminator for Constructors 14
3.3 The Initial Algebra: A Quotiented Message Type 14
3.3.1 Characteristic Equations for the Abstract Constructors 15

3.4 The Abstract Function to Return the Set of Nonces 16
3.5 The Abstract Function to Return the Left Part 17
3.6 The Abstract Function to Return the Right Part 18
3.7 Injectivity Properties of Some Constructors 18
3.8 The Abstract Discriminator 20

4 Quotienting a Free Algebra Involving Nested Recursion 21
4.1 Defining the Free Algebra 21
4.2 Some Functions on the Free Algebra 22
4.2.1 The Set of Variables 22
4.2.2 Functions for Freeness 23
4.3 The Initial Algebra: A Quotiented Message Type 24
4.4 Every list of abstract expressions can be expressed in terms of a list of concrete expressions 25
4.4.1 Characteristic Equations for the Abstract Constructors 25
4.5 The Abstract Function to Return the Set of Variables 26
4.6 Injectivity Properties of Some Constructors 27
4.7 Injectivity of *FnCall* 28
4.8 The Abstract Discriminator 29

5 Terms over a given alphabet 30

6 Extended List Theory (old) 34

7 Arithmetic and boolean expressions 42

8 Infinitely branching trees 43
8.1 The Brouwer ordinals, as in ZF/Induct/Brouwer.thy. 44
8.2 A WF Ordering for The Brouwer ordinals (Michael Compton) 45

9 Ordinals 45

10 Sigma algebras 47

11 Combinatory Logic example: the Church-Rosser Theorem 47
11.1 Definitions 48
11.2 Reflexive/Transitive closure preserves Church-Rosser property 49
11.3 Non-contraction results 49
11.4 Results about Parallel Contraction 50
11.5 Basic properties of parallel contraction 50
11.6 Equivalence of $p \to q$ and $p \Rrightarrow q$. 51

12 Meta-theory of propositional logic **51**
12.1 The datatype of propositions 51
12.2 The proof system 52
12.3 The semantics 52
12.3.1 Semantics of propositional logic. 52
12.3.2 Logical consequence 52
12.4 Proof theory of propositional logic 52
12.4.1 Weakening, left and right 52
12.4.2 The deduction theorem 53
12.4.3 The cut rule 53
12.4.4 Soundness of the rules wrt truth-table semantics . . . 53
12.5 Completeness 53
12.5.1 Towards the completeness proof 53
12.6 Completeness – lemmas for reducing the set of assumptions . 54
12.6.1 Completeness theorem 55

13 Mutual Induction via Iteratived Inductive Definitions **56**
13.1 Commands 56
13.2 Expressions 58
13.3 Equivalence of IF e THEN c;;(WHILE e DO c) ELSE SKIP and WHILE e DO c 60
13.4 Equivalence of (IF e THEN c1 ELSE c2);;c and IF e THEN (c1;;c) ELSE (c2;;c) 60
13.5 Equivalence of VALOF c1 RESULTIS (VALOF c2 RESULTIS e) and VALOF c1;;c2 RESULTIS e 61
13.6 Equivalence of VALOF SKIP RESULTIS e and e 61
13.7 Equivalence of VALOF x:=e RESULTIS x and e 61

1 Common patterns of induction

theory *Common-Patterns*
imports *Main*
begin

The subsequent Isar proof schemes illustrate common proof patterns supported by the generic *induct* method.

To demonstrate variations on statement (goal) structure we refer to the induction rule of Peano natural numbers: $[\![P\ 0;\ \bigwedge nat.\ P\ nat \Longrightarrow P\ (Suc\ nat)]\!] \Longrightarrow P\ nat$, which is the simplest case of datatype induction. We shall also see more complex (mutual) datatype inductions involving several rules. Working with inductive predicates is similar, but involves explicit facts about membership, instead of implicit syntactic typing.

1.1 Variations on statement structure

1.1.1 Local facts and parameters

Augmenting a problem by additional facts and locally fixed variables is a bread-and-butter method in many applications. This is where unwieldy object-level $\forall$ and $\longrightarrow$ used to occur in the past. The *induct* method works with primary means of the proof language instead.

```
lemma
  fixes n :: nat
    and x :: 'a
  assumes A n x
  shows P n x using ‹A n x›
proof (induct n arbitrary: x)
  case 0
  note prem = ‹A 0 x›
  show P 0 x ⟨proof⟩
next
  case (Suc n)
  note hyp = ‹⋀x. A n x ⟹ P n x›
    and prem = ‹A (Suc n) x›
  show P (Suc n) x ⟨proof⟩
qed
```

1.1.2 Local definitions

Here the idea is to turn sub-expressions of the problem into a defined induction variable. This is often accompanied with fixing of auxiliary parameters in the original expression, otherwise the induction step would refer invariably to particular entities. This combination essentially expresses a partially abstracted representation of inductive expressions.

lemma

```
  fixes a :: 'a ⇒ nat
  assumes A (a x)
  shows P (a x) using ‹A (a x)›
proof (induct n ≡ a x arbitrary: x)
  case 0
  note prem = ‹A (a x)›
    and defn = ‹0 = a x›
  show P (a x) ⟨proof⟩
next
  case (Suc n)
  note hyp = ‹⋀x. n = a x ⟹ A (a x) ⟹ P (a x)›
    and prem = ‹A (a x)›
    and defn = ‹Suc n = a x›
  show P (a x) ⟨proof⟩
qed
```

Observe how the local definition $n = a\ x$ recurs in the inductive cases as $0 = a\ x$ and $Suc\ n = a\ x$, according to underlying induction rule.

1.1.3 Simple simultaneous goals

The most basic simultaneous induction operates on several goals one-by-one, where each case refers to induction hypotheses that are duplicated according to the number of conclusions.

```
lemma
  fixes n :: nat
  shows P n and Q n
proof (induct n)
  case 0 case 1
  show P 0 ⟨proof⟩
next
  case 0 case 2
  show Q 0 ⟨proof⟩
next
  case (Suc n) case 1
  note hyps = ‹P n› ‹Q n›
  show P (Suc n) ⟨proof⟩
next
  case (Suc n) case 2
  note hyps = ‹P n› ‹Q n›
  show Q (Suc n) ⟨proof⟩
qed
```

The split into subcases may be deferred as follows – this is particularly relevant for goal statements with local premises.

```
lemma
  fixes n :: nat
  shows A n ⟹ P n
```

```
    and B n ⟹ Q n
proof (induct n)
  case 0
  {
    case 1
    note ‹A 0›
    show P 0 ⟨proof⟩
  next
    case 2
    note ‹B 0›
    show Q 0 ⟨proof⟩
  }
next
  case (Suc n)
  note ‹A n ⟹ P n›
    and ‹B n ⟹ Q n›
  {
    case 1
    note ‹A (Suc n)›
    show P (Suc n) ⟨proof⟩
  next
    case 2
    note ‹B (Suc n)›
    show Q (Suc n) ⟨proof⟩
  }
qed
```

1.1.4 Compound simultaneous goals

The following pattern illustrates the slightly more complex situation of simultaneous goals with individual local assumptions. In compound simultaneous statements like this, local assumptions need to be included into each goal, using ⟹ of the Pure framework. In contrast, local parameters do not require separate ⋀ prefixes here, but may be moved into the common context of the whole statement.

```
lemma
  fixes n :: nat
    and x :: 'a
    and y :: 'b
  shows A n x ⟹ P n x
    and B n y ⟹ Q n y
proof (induct n arbitrary: x y)
  case 0
  {
    case 1
    note prem = ‹A 0 x›
    show P 0 x ⟨proof⟩
  }
```

```
  {
    case 2
    note prem = ‹B 0 y›
    show Q 0 y ⟨proof⟩
  }
next
  case (Suc n)
  note hyps = ‹⋀x. A n x ⟹ P n x› ‹⋀y. B n y ⟹ Q n y›
  then have some-intermediate-result ⟨proof⟩
  {
    case 1
    note prem = ‹A (Suc n) x›
    show P (Suc n) x ⟨proof⟩
  }
  {
    case 2
    note prem = ‹B (Suc n) y›
    show Q (Suc n) y ⟨proof⟩
  }
qed
```

Here *induct* provides again nested cases with numbered sub-cases, which allows to share common parts of the body context. In typical applications, there could be a long intermediate proof of general consequences of the induction hypotheses, before finishing each conclusion separately.

1.2 Multiple rules

Multiple induction rules emerge from mutual definitions of datatypes, inductive predicates, functions etc. The *induct* method accepts replicated arguments (with *and* separator), corresponding to each projection of the induction principle.

The goal statement essentially follows the same arrangement, although it might be subdivided into simultaneous sub-problems as before!

```
datatype foo = Foo1 nat | Foo2 bar
  and bar = Bar1 bool | Bar2 bazar
  and bazar = Bazar foo
```

The pack of induction rules for this datatype is:

```
⟦⋀x. P1 (Foo1 x); ⋀x. P2 x ⟹ P1 (Foo2 x); ⋀x. P2 (Bar1 x);
 ⋀x. P3 x ⟹ P2 (Bar2 x); ⋀x. P1 x ⟹ P3 (Bazar x)⟧
⟹ P1 foo
⟦⋀x. P1 (Foo1 x); ⋀x. P2 x ⟹ P1 (Foo2 x); ⋀x. P2 (Bar1 x);
 ⋀x. P3 x ⟹ P2 (Bar2 x); ⋀x. P1 x ⟹ P3 (Bazar x)⟧
⟹ P2 bar
⟦⋀x. P1 (Foo1 x); ⋀x. P2 x ⟹ P1 (Foo2 x); ⋀x. P2 (Bar1 x);
 ⋀x. P3 x ⟹ P2 (Bar2 x); ⋀x. P1 x ⟹ P3 (Bazar x)⟧
```

$\Longrightarrow$ *P3 bazar*

This corresponds to the following basic proof pattern:

```
lemma
  fixes foo :: foo
    and bar :: bar
    and bazar :: bazar
  shows P foo
    and Q bar
    and R bazar
proof (induct foo and bar and bazar)
  case (Foo1 n)
  show P (Foo1 n) ⟨proof⟩
next
  case (Foo2 bar)
  note ‹Q bar›
  show P (Foo2 bar) ⟨proof⟩
next
  case (Bar1 b)
  show Q (Bar1 b) ⟨proof⟩
next
  case (Bar2 bazar)
  note ‹R bazar›
  show Q (Bar2 bazar) ⟨proof⟩
next
  case (Bazar foo)
  note ‹P foo›
  show R (Bazar foo) ⟨proof⟩
qed
```

This can be combined with the previous techniques for compound statements, e.g. like this.

```
lemma
  fixes x :: 'a and y :: 'b and z :: 'c
    and foo :: foo
    and bar :: bar
    and bazar :: bazar
  shows
    A x foo ⟹ P x foo
  and
    B1 y bar ⟹ Q1 y bar
    B2 y bar ⟹ Q2 y bar
  and
    C1 z bazar ⟹ R1 z bazar
    C2 z bazar ⟹ R2 z bazar
    C3 z bazar ⟹ R3 z bazar
proof (induct foo and bar and bazar arbitrary: x and y and z)
  oops
```

1.3 Inductive predicates

The most basic form of induction involving predicates (or sets) essentially eliminates a given membership fact.

```
inductive Even :: nat ⇒ bool where
  zero: Even 0
| double: Even (2 ∗ n) if Even n for n

lemma
  assumes Even n
  shows P n
  using assms
proof induct
  case zero
  show P 0 ⟨proof⟩
next
  case (double n)
  note ‹Even n› and ‹P n›
  show P (2 ∗ n) ⟨proof⟩
qed
```

Alternatively, an initial rule statement may be proven as follows, performing "in-situ" elimination with explicit rule specification.

```
lemma Even n ⟹ P n
proof (induct rule: Even.induct)
  oops
```

Simultaneous goals do not introduce anything new.

```
lemma
  assumes Even n
  shows P1 n and P2 n
  using assms
proof induct
  case zero
  {
    case 1
    show P1 0 ⟨proof⟩
  next
    case 2
    show P2 0 ⟨proof⟩
  }
next
  case (double n)
  note ‹Even n› and ‹P1 n› and ‹P2 n›
  {
    case 1
    show P1 (2 ∗ n) ⟨proof⟩
  next
```

```
    case 2
    show P2 (2 * n) ⟨proof⟩
  }
qed
```

Working with mutual rules requires special care in composing the statement as a two-level conjunction, using lists of propositions separated by *and*. For example:

```
inductive Evn :: nat ⇒ bool and Odd :: nat ⇒ bool
where
  zero: Evn 0
| succ-Evn: Odd (Suc n) if Evn n for n
| succ-Odd: Evn (Suc n) if Odd n for n

lemma
    Evn n ⟹ P1 n
    Evn n ⟹ P2 n
    Evn n ⟹ P3 n
  and
    Odd n ⟹ Q1 n
    Odd n ⟹ Q2 n
proof (induct rule: Evn-Odd.inducts)
  case zero
  { case 1 show P1 0 ⟨proof⟩ }
  { case 2 show P2 0 ⟨proof⟩ }
  { case 3 show P3 0 ⟨proof⟩ }
next
  case (succ-Evn n)
  note ‹Evn n› and ‹P1 n› ‹P2 n› ‹P3 n›
  { case 1 show Q1 (Suc n) ⟨proof⟩ }
  { case 2 show Q2 (Suc n) ⟨proof⟩ }
next
  case (succ-Odd n)
  note ‹Odd n› and ‹Q1 n› ‹Q2 n›
  { case 1 show P1 (Suc n) ⟨proof⟩ }
  { case 2 show P2 (Suc n) ⟨proof⟩ }
  { case 3 show P3 (Suc n) ⟨proof⟩ }
qed
```

Cases and hypotheses in each case can be named explicitly.

```
inductive star :: ('a ⇒ 'a ⇒ bool) ⇒ 'a ⇒ 'a ⇒ bool for r
where
  refl: star r x x for x
| step: star r x z if r x y and star r y z for x y z
```

Underscores are replaced by the default name hyps:

```
lemmas star-induct = star.induct [case-names base step[r - IH]]
```

lemma *star r x y* $\Longrightarrow$ *star r y z* $\Longrightarrow$ *star r x z*
proof (*induct rule*: *star-induct*) **print-cases**
  case *base*
  then show *?case* **.**
next
  case (*step a b c*) **print-facts**
  from *step.prems* **have** *star r b z* **by** (*rule step.IH*)
  with *step.r* **show** *?case* **by** (*rule star.step*)
qed

end

2 Nested datatypes

theory *Nested-Datatype*
imports *Main*
begin

2.1 Terms and substitution

datatype ('*a*, '*b*) *term* =
  Var '*a*
| *App* '*b* ('*a*, '*b*) *term list*

primrec *subst-term* :: ('*a* $\Rightarrow$ ('*a*, '*b*) *term*) $\Rightarrow$ ('*a*, '*b*) *term* $\Rightarrow$ ('*a*, '*b*) *term*
  and *subst-term-list* :: ('*a* $\Rightarrow$ ('*a*, '*b*) *term*) $\Rightarrow$ ('*a*, '*b*) *term list* $\Rightarrow$ ('*a*, '*b*) *term list*
where
  subst-term f (*Var a*) = *f a*
| *subst-term f* (*App b ts*) = *App b* (*subst-term-list f ts*)
| *subst-term-list f* [] = []
| *subst-term-list f* (*t* # *ts*) = *subst-term f t* # *subst-term-list f ts*

lemmas *subst-simps* = *subst-term.simps subst-term-list.simps*

A simple lemma about composition of substitutions.

lemma
  subst-term (*subst-term f1* $\circ$ *f2*) *t* =
    subst-term f1 (*subst-term f2 t*)
  and
  subst-term-list (*subst-term f1* $\circ$ *f2*) *ts* =
    subst-term-list f1 (*subst-term-list f2 ts*)
  by (*induct t* **and** *ts rule*: *subst-term.induct subst-term-list.induct*) *simp-all*

lemma *subst-term* (*subst-term f1* $\circ$ *f2*) *t* = *subst-term f1* (*subst-term f2 t*)
proof −
  let *?P t* = *?thesis*
  let *?Q* = λ*ts*. *subst-term-list* (*subst-term f1* $\circ$ *f2*) *ts* =

```
    subst-term-list f1 (subst-term-list f2 ts)
  show ?thesis
  proof (induct t rule: subst-term.induct)
    show ?P (Var a) for a by simp
    show ?P (App b ts) if ?Q ts for b ts
      using that by (simp only: subst-simps)
    show ?Q [] by simp
    show ?Q (t # ts) if ?P t ?Q ts for t ts
      using that by (simp only: subst-simps)
  qed
qed
```

2.2 Alternative induction

```
lemma subst-term (subst-term f1 ∘ f2) t = subst-term f1 (subst-term f2 t)
proof (induct t rule: term.induct)
  case (Var a)
  show ?case by (simp add: o-def)
next
  case (App b ts)
  then show ?case by (induct ts) simp-all
qed

end
```

3 Defining an Initial Algebra by Quotienting a Free Algebra

```
theory QuoDataType imports Main begin
```

3.1 Defining the Free Algebra

Messages with encryption and decryption as free constructors.

```
datatype
    freemsg = NONCE nat
            | MPAIR freemsg freemsg
            | CRYPT nat freemsg
            | DECRYPT nat freemsg
```

The equivalence relation, which makes encryption and decryption inverses provided the keys are the same.

The first two rules are the desired equations. The next four rules make the equations applicable to subterms. The last two rules are symmetry and transitivity.

```
inductive-set
  msgrel :: (freemsg * freemsg) set
  and msg-rel :: [freemsg, freemsg] => bool (infixl ~ 50)
```

where
  $X \sim Y == (X, Y) \in msgrel$
| CD: $CRYPT\ K\ (DECRYPT\ K\ X) \sim X$
| DC: $DECRYPT\ K\ (CRYPT\ K\ X) \sim X$
| $NONCE$: $NONCE\ N \sim NONCE\ N$
| $MPAIR$: $[\![X \sim X'; Y \sim Y']\!] \Longrightarrow MPAIR\ X\ Y \sim MPAIR\ X'\ Y'$
| $CRYPT$: $X \sim X' \Longrightarrow CRYPT\ K\ X \sim CRYPT\ K\ X'$
| $DECRYPT$: $X \sim X' \Longrightarrow DECRYPT\ K\ X \sim DECRYPT\ K\ X'$
| SYM: $X \sim Y \Longrightarrow Y \sim X$
| $TRANS$: $[\![X \sim Y; Y \sim Z]\!] \Longrightarrow X \sim Z$

Proving that it is an equivalence relation

lemma *msgrel-refl*: $X \sim X$
  by (*induct X*) (*blast intro*: *msgrel.intros*)+

theorem *equiv-msgrel*: *equiv UNIV msgrel*
proof −
  have *refl msgrel* **by** (*simp add*: *refl-on-def msgrel-refl*)
  moreover have *sym msgrel* **by** (*simp add*: *sym-def*, *blast intro*: *msgrel.SYM*)
  moreover have *trans msgrel* **by** (*simp add*: *trans-def*, *blast intro*: *msgrel.TRANS*)
  ultimately show *?thesis* **by** (*simp add*: *equiv-def*)
qed

3.2 Some Functions on the Free Algebra

3.2.1 The Set of Nonces

A function to return the set of nonces present in a message. It will be lifted to the initial algebra, to serve as an example of that process.

primrec *freenonces* :: *freemsg* ⇒ *nat set* **where**
  $freenonces\ (NONCE\ N) = \{N\}$
| $freenonces\ (MPAIR\ X\ Y) = freenonces\ X \cup freenonces\ Y$
| $freenonces\ (CRYPT\ K\ X) = freenonces\ X$
| $freenonces\ (DECRYPT\ K\ X) = freenonces\ X$

This theorem lets us prove that the nonces function respects the equivalence relation. It also helps us prove that Nonce (the abstract constructor) is injective

theorem *msgrel-imp-eq-freenonces*: $U \sim V \Longrightarrow freenonces\ U = freenonces\ V$
  by (*induct set*: *msgrel*) *auto*

3.2.2 The Left Projection

A function to return the left part of the top pair in a message. It will be lifted to the initial algebra, to serve as an example of that process.

primrec *freeleft* :: *freemsg* ⇒ *freemsg* **where**
  $freeleft\ (NONCE\ N) = NONCE\ N$

| *freeleft* (*MPAIR X Y*) = *X*
| *freeleft* (*CRYPT K X*) = *freeleft X*
| *freeleft* (*DECRYPT K X*) = *freeleft X*

This theorem lets us prove that the left function respects the equivalence relation. It also helps us prove that MPair (the abstract constructor) is injective

theorem *msgrel-imp-eqv-freeleft*:
  $U \sim V \Longrightarrow$ *freeleft U* $\sim$ *freeleft V*
  by (*induct set*: *msgrel*) (*auto intro*: *msgrel.intros*)

3.2.3 The Right Projection

A function to return the right part of the top pair in a message.

primrec *freeright* :: *freemsg* $\Rightarrow$ *freemsg* **where**
  freeright (*NONCE N*) = *NONCE N*
| *freeright* (*MPAIR X Y*) = *Y*
| *freeright* (*CRYPT K X*) = *freeright X*
| *freeright* (*DECRYPT K X*) = *freeright X*

This theorem lets us prove that the right function respects the equivalence relation. It also helps us prove that MPair (the abstract constructor) is injective

theorem *msgrel-imp-eqv-freeright*:
  $U \sim V \Longrightarrow$ *freeright U* $\sim$ *freeright V*
  by (*induct set*: *msgrel*) (*auto intro*: *msgrel.intros*)

3.2.4 The Discriminator for Constructors

A function to distinguish nonces, mpairs and encryptions

primrec *freediscrim* :: *freemsg* $\Rightarrow$ *int* **where**
  freediscrim (*NONCE N*) = *0*
| *freediscrim* (*MPAIR X Y*) = *1*
| *freediscrim* (*CRYPT K X*) = *freediscrim X* + *2*
| *freediscrim* (*DECRYPT K X*) = *freediscrim X* − *2*

This theorem helps us prove *Nonce N* $\neq$ *MPair X Y*

theorem *msgrel-imp-eq-freediscrim*:
  $U \sim V \Longrightarrow$ *freediscrim U* = *freediscrim V*
  by (*induct set*: *msgrel*) *auto*

3.3 The Initial Algebra: A Quotiented Message Type

definition *Msg* = *UNIV*//*msgrel*

typedef *msg* = *Msg*
  morphisms *Rep-Msg Abs-Msg*

unfolding *Msg-def* **by** (*auto simp add*: *quotient-def*)

The abstract message constructors

definition
Nonce :: *nat* ⇒ *msg* **where**
Nonce N = *Abs-Msg*(*msgrel*``{*NONCE N*})

definition
MPair :: [*msg*,*msg*] ⇒ *msg* **where**
MPair X Y =
Abs-Msg (⋃ *U* ∈ *Rep-Msg X*. ⋃ *V* ∈ *Rep-Msg Y*. *msgrel*``{*MPAIR U V*})

definition
Crypt :: [*nat*,*msg*] ⇒ *msg* **where**
Crypt K X =
Abs-Msg (⋃ *U* ∈ *Rep-Msg X*. *msgrel*``{*CRYPT K U*})

definition
Decrypt :: [*nat*,*msg*] ⇒ *msg* **where**
Decrypt K X =
Abs-Msg (⋃ *U* ∈ *Rep-Msg X*. *msgrel*``{*DECRYPT K U*})

Reduces equality of equivalence classes to the *msgrel* relation: (*msgrel* `` {*x*} = *msgrel* `` {*y*}) = (*x* ∼ *y*)

lemmas *equiv-msgrel-iff* = *eq-equiv-class-iff* [*OF equiv-msgrel UNIV-I UNIV-I*]

declare *equiv-msgrel-iff* [*simp*]

All equivalence classes belong to set of representatives

lemma [*simp*]: *msgrel*``{*U*} ∈ *Msg*
by (*auto simp add*: *Msg-def quotient-def intro*: *msgrel-refl*)

lemma *inj-on-Abs-Msg*: *inj-on Abs-Msg Msg*
apply (*rule inj-on-inverseI*)
apply (*erule Abs-Msg-inverse*)
done

Reduces equality on abstractions to equality on representatives

declare *inj-on-Abs-Msg* [*THEN inj-on-eq-iff*, *simp*]

declare *Abs-Msg-inverse* [*simp*]

3.3.1 Characteristic Equations for the Abstract Constructors

lemma *MPair*: *MPair* (*Abs-Msg*(*msgrel*``{*U*})) (*Abs-Msg*(*msgrel*``{*V*})) =
Abs-Msg (*msgrel*``{*MPAIR U V*})
proof −
have (λ*U V*. *msgrel* `` {*MPAIR U V*}) *respects2 msgrel*

by (*auto simp add*: *congruent2-def msgrel.MPAIR*)
thus *?thesis*
by (*simp add*: *MPair-def UN-equiv-class2* [*OF equiv-msgrel equiv-msgrel*])
qed

lemma *Crypt*: *Crypt K* (*Abs-Msg*(*msgrel*``{*U*})) = *Abs-Msg* (*msgrel*``{*CRYPT K U*})
proof −
have (λ*U*. *msgrel* `` {*CRYPT K U*}) *respects msgrel*
by (*auto simp add*: *congruent-def msgrel.CRYPT*)
thus *?thesis*
by (*simp add*: *Crypt-def UN-equiv-class* [*OF equiv-msgrel*])
qed

lemma *Decrypt*:
Decrypt K (*Abs-Msg*(*msgrel*``{*U*})) = *Abs-Msg* (*msgrel*``{*DECRYPT K U*})
proof −
have (λ*U*. *msgrel* `` {*DECRYPT K U*}) *respects msgrel*
by (*auto simp add*: *congruent-def msgrel.DECRYPT*)
thus *?thesis*
by (*simp add*: *Decrypt-def UN-equiv-class* [*OF equiv-msgrel*])
qed

Case analysis on the representation of a msg as an equivalence class.

lemma *eq-Abs-Msg* [*case-names Abs-Msg*, *cases type*: *msg*]:
(!!*U*. *z* = *Abs-Msg*(*msgrel*``{*U*}) ==> *P*) ==> *P*
apply (*rule Rep-Msg* [*of z*, *unfolded Msg-def*, *THEN quotientE*])
apply (*drule arg-cong* [**where** *f*=*Abs-Msg*])
apply (*auto simp add*: *Rep-Msg-inverse intro*: *msgrel-refl*)
done

Establishing these two equations is the point of the whole exercise

theorem *CD-eq* [*simp*]: *Crypt K* (*Decrypt K X*) = *X*
by (*cases X*, *simp add*: *Crypt Decrypt CD*)

theorem *DC-eq* [*simp*]: *Decrypt K* (*Crypt K X*) = *X*
by (*cases X*, *simp add*: *Crypt Decrypt DC*)

3.4 The Abstract Function to Return the Set of Nonces

definition
nonces :: *msg* ⇒ *nat set* **where**
nonces X = (⋃ *U* ∈ *Rep-Msg X*. *freenonces U*)

lemma *nonces-congruent*: *freenonces respects msgrel*
by (*auto simp add*: *congruent-def msgrel-imp-eq-freenonces*)

Now prove the four equations for *nonces*

lemma *nonces-Nonce* [*simp*]: *nonces* (*Nonce N*) = {*N*}

by (*simp add*: *nonces-def Nonce-def*
UN-equiv-class [*OF equiv-msgrel nonces-congruent*])

lemma *nonces-MPair* [*simp*]: *nonces* (*MPair X Y*) = *nonces X* ∪ *nonces Y*
apply (*cases X*, *cases Y*)
apply (*simp add*: *nonces-def MPair*
UN-equiv-class [*OF equiv-msgrel nonces-congruent*])
done

lemma *nonces-Crypt* [*simp*]: *nonces* (*Crypt K X*) = *nonces X*
apply (*cases X*)
apply (*simp add*: *nonces-def Crypt*
UN-equiv-class [*OF equiv-msgrel nonces-congruent*])
done

lemma *nonces-Decrypt* [*simp*]: *nonces* (*Decrypt K X*) = *nonces X*
apply (*cases X*)
apply (*simp add*: *nonces-def Decrypt*
UN-equiv-class [*OF equiv-msgrel nonces-congruent*])
done

3.5 The Abstract Function to Return the Left Part

definition
left :: *msg* ⇒ *msg* **where**
left X = *Abs-Msg* (⋃ *U* ∈ *Rep-Msg X*. *msgrel*``{*freeleft U*})

lemma *left-congruent*: (λ*U*. *msgrel* `` {*freeleft U*}) *respects msgrel*
by (*auto simp add*: *congruent-def msgrel-imp-eqv-freeleft*)

Now prove the four equations for *left*

lemma *left-Nonce* [*simp*]: *left* (*Nonce N*) = *Nonce N*
by (*simp add*: *left-def Nonce-def*
UN-equiv-class [*OF equiv-msgrel left-congruent*])

lemma *left-MPair* [*simp*]: *left* (*MPair X Y*) = *X*
apply (*cases X*, *cases Y*)
apply (*simp add*: *left-def MPair*
UN-equiv-class [*OF equiv-msgrel left-congruent*])
done

lemma *left-Crypt* [*simp*]: *left* (*Crypt K X*) = *left X*
apply (*cases X*)
apply (*simp add*: *left-def Crypt*
UN-equiv-class [*OF equiv-msgrel left-congruent*])
done

lemma *left-Decrypt* [*simp*]: *left* (*Decrypt K X*) = *left X*
apply (*cases X*)

apply (*simp add*: *left-def Decrypt*
UN-equiv-class [*OF equiv-msgrel left-congruent*])
done

3.6 The Abstract Function to Return the Right Part

definition
right :: *msg* ⇒ *msg* **where**
right X = *Abs-Msg* (⋃ *U* ∈ *Rep-Msg X*. *msgrel*``{*freeright U*})

lemma *right-congruent*: (λ*U*. *msgrel* `` {*freeright U*}) *respects msgrel*
by (*auto simp add*: *congruent-def msgrel-imp-eqv-freeright*)

Now prove the four equations for *right*

lemma *right-Nonce* [*simp*]: *right* (*Nonce N*) = *Nonce N*
by (*simp add*: *right-def Nonce-def*
UN-equiv-class [*OF equiv-msgrel right-congruent*])

lemma *right-MPair* [*simp*]: *right* (*MPair X Y*) = *Y*
apply (*cases X*, *cases Y*)
apply (*simp add*: *right-def MPair*
UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

lemma *right-Crypt* [*simp*]: *right* (*Crypt K X*) = *right X*
apply (*cases X*)
apply (*simp add*: *right-def Crypt*
UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

lemma *right-Decrypt* [*simp*]: *right* (*Decrypt K X*) = *right X*
apply (*cases X*)
apply (*simp add*: *right-def Decrypt*
UN-equiv-class [*OF equiv-msgrel right-congruent*])
done

3.7 Injectivity Properties of Some Constructors

lemma *NONCE-imp-eq*: *NONCE m* ∼ *NONCE n* ⟹ *m* = *n*
by (*drule msgrel-imp-eq-freenonces*, *simp*)

Can also be proved using the function *nonces*

lemma *Nonce-Nonce-eq* [*iff*]: (*Nonce m* = *Nonce n*) = (*m* = *n*)
by (*auto simp add*: *Nonce-def msgrel-refl dest*: *NONCE-imp-eq*)

lemma *MPAIR-imp-eqv-left*: *MPAIR X Y* ∼ *MPAIR X′ Y′* ⟹ *X* ∼ *X′*
by (*drule msgrel-imp-eqv-freeleft*, *simp*)

lemma *MPair-imp-eq-left*:

assumes *eq*: *MPair X Y* = *MPair X′ Y′* **shows** *X* = *X′*
proof −
from *eq*
have *left* (*MPair X Y*) = *left* (*MPair X′ Y′*) **by** *simp*
thus *?thesis* **by** *simp*
qed

lemma *MPAIR-imp-eqv-right*: *MPAIR X Y* ∼ *MPAIR X′ Y′* ⟹ *Y* ∼ *Y′*
by (*drule msgrel-imp-eqv-freeright*, *simp*)

lemma *MPair-imp-eq-right*: *MPair X Y* = *MPair X′ Y′* ⟹ *Y* = *Y′*
apply (*cases X*, *cases X′*, *cases Y*, *cases Y′*)
apply (*simp add*: *MPair*)
apply (*erule MPAIR-imp-eqv-right*)
done

theorem *MPair-MPair-eq* [*iff*]: (*MPair X Y* = *MPair X′ Y′*) = (*X*=*X′* & *Y*=*Y′*)
by (*blast dest*: *MPair-imp-eq-left MPair-imp-eq-right*)

lemma *NONCE-neqv-MPAIR*: *NONCE m* ∼ *MPAIR X Y* ⟹ *False*
by (*drule msgrel-imp-eq-freediscrim*, *simp*)

theorem *Nonce-neq-MPair* [*iff*]: *Nonce N* ≠ *MPair X Y*
apply (*cases X*, *cases Y*)
apply (*simp add*: *Nonce-def MPair*)
apply (*blast dest*: *NONCE-neqv-MPAIR*)
done

Example suggested by a referee

theorem *Crypt-Nonce-neq-Nonce*: *Crypt K* (*Nonce M*) ≠ *Nonce N*
by (*auto simp add*: *Nonce-def Crypt dest*: *msgrel-imp-eq-freediscrim*)

...and many similar results

theorem *Crypt2-Nonce-neq-Nonce*: *Crypt K* (*Crypt K′* (*Nonce M*)) ≠ *Nonce N*
by (*auto simp add*: *Nonce-def Crypt dest*: *msgrel-imp-eq-freediscrim*)

theorem *Crypt-Crypt-eq* [*iff*]: (*Crypt K X* = *Crypt K X′*) = (*X*=*X′*)
proof
assume *Crypt K X* = *Crypt K X′*
hence *Decrypt K* (*Crypt K X*) = *Decrypt K* (*Crypt K X′*) **by** *simp*
thus *X* = *X′* **by** *simp*
next
assume *X* = *X′*
thus *Crypt K X* = *Crypt K X′* **by** *simp*
qed

theorem *Decrypt-Decrypt-eq* [*iff*]: (*Decrypt K X* = *Decrypt K X′*) = (*X*=*X′*)
proof

```
  assume Decrypt K X = Decrypt K X'
  hence Crypt K (Decrypt K X) = Crypt K (Decrypt K X') by simp
  thus X = X' by simp
next
  assume X = X'
  thus Decrypt K X = Decrypt K X' by simp
qed

lemma msg-induct [case-names Nonce MPair Crypt Decrypt, cases type: msg]:
  assumes N: ⋀N. P (Nonce N)
      and M: ⋀X Y. ⟦P X; P Y⟧ ⟹ P (MPair X Y)
      and C: ⋀K X. P X ⟹ P (Crypt K X)
      and D: ⋀K X. P X ⟹ P (Decrypt K X)
  shows P msg
proof (cases msg)
  case (Abs-Msg U)
  have P (Abs-Msg (msgrel `` {U}))
  proof (induct U)
    case (NONCE N)
    with N show ?case by (simp add: Nonce-def)
  next
    case (MPAIR X Y)
    with M [of Abs-Msg (msgrel `` {X}) Abs-Msg (msgrel `` {Y})]
    show ?case by (simp add: MPair)
  next
    case (CRYPT K X)
    with C [of Abs-Msg (msgrel `` {X})]
    show ?case by (simp add: Crypt)
  next
    case (DECRYPT K X)
    with D [of Abs-Msg (msgrel `` {X})]
    show ?case by (simp add: Decrypt)
  qed
  with Abs-Msg show ?thesis by (simp only:)
qed
```

3.8 The Abstract Discriminator

However, as *Crypt-Nonce-neq-Nonce* above illustrates, we don't need this function in order to prove discrimination theorems.

```
definition
  discrim :: msg ⇒ int where
   discrim X = the-elem (⋃U ∈ Rep-Msg X. {freediscrim U})

lemma discrim-congruent: (λU. {freediscrim U}) respects msgrel
by (auto simp add: congruent-def msgrel-imp-eq-freediscrim)
```

Now prove the four equations for *discrim*

```
lemma discrim-Nonce [simp]: discrim (Nonce N) = 0
```

by (*simp add*: *discrim-def Nonce-def*
UN-equiv-class [*OF equiv-msgrel discrim-congruent*])

lemma *discrim-MPair* [*simp*]: *discrim* (*MPair X Y*) = *1*
apply (*cases X*, *cases Y*)
apply (*simp add*: *discrim-def MPair*
UN-equiv-class [*OF equiv-msgrel discrim-congruent*])
done

lemma *discrim-Crypt* [*simp*]: *discrim* (*Crypt K X*) = *discrim X* + *2*
apply (*cases X*)
apply (*simp add*: *discrim-def Crypt*
UN-equiv-class [*OF equiv-msgrel discrim-congruent*])
done

lemma *discrim-Decrypt* [*simp*]: *discrim* (*Decrypt K X*) = *discrim X* − *2*
apply (*cases X*)
apply (*simp add*: *discrim-def Decrypt*
UN-equiv-class [*OF equiv-msgrel discrim-congruent*])
done

end

4 Quotienting a Free Algebra Involving Nested Recursion

theory *QuoNestedDataType* **imports** *Main* **begin**

4.1 Defining the Free Algebra

Messages with encryption and decryption as free constructors.

datatype
freeExp = *VAR nat*
| *PLUS freeExp freeExp*
| *FNCALL nat freeExp list*

datatype-compat *freeExp*

The equivalence relation, which makes PLUS associative.

The first rule is the desired equation. The next three rules make the equations applicable to subterms. The last two rules are symmetry and transitivity.

inductive-set
exprel :: (*freeExp* ∗ *freeExp*) *set*
and *exp-rel* :: [*freeExp*, *freeExp*] => *bool* (**infixl** ∼ *50*)

where
$X \sim Y == (X,Y) \in exprel$
| *ASSOC*: $PLUS\ X\ (PLUS\ Y\ Z) \sim PLUS\ (PLUS\ X\ Y)\ Z$
| *VAR*: $VAR\ N \sim VAR\ N$
| *PLUS*: $[\![X \sim X';\ Y \sim Y']\!] \Longrightarrow PLUS\ X\ Y \sim PLUS\ X'\ Y'$
| *FNCALL*: $(Xs,Xs') \in listrel\ exprel \Longrightarrow FNCALL\ F\ Xs \sim FNCALL\ F\ Xs'$
| *SYM*: $X \sim Y \Longrightarrow Y \sim X$
| *TRANS*: $[\![X \sim Y;\ Y \sim Z]\!] \Longrightarrow X \sim Z$
monos *listrel-mono*

Proving that it is an equivalence relation

lemma *exprel-refl*: $X \sim X$
and *list-exprel-refl*: $(Xs,Xs) \in listrel(exprel)$
by (*induct X* **and** *Xs rule*: *compat-freeExp.induct compat-freeExp-list.induct*)
(*blast intro*: *exprel.intros listrel.intros*)+

theorem *equiv-exprel*: *equiv UNIV exprel*
proof −
have *refl exprel* **by** (*simp add*: *refl-on-def exprel-refl*)
moreover have *sym exprel* **by** (*simp add*: *sym-def*, *blast intro*: *exprel.SYM*)
moreover have *trans exprel* **by** (*simp add*: *trans-def*, *blast intro*: *exprel.TRANS*)
ultimately show *?thesis* **by** (*simp add*: *equiv-def*)
qed

theorem *equiv-list-exprel*: *equiv UNIV* (*listrel exprel*)
using *equiv-listrel* [*OF equiv-exprel*] **by** *simp*

lemma *FNCALL-Nil*: $FNCALL\ F\ [] \sim FNCALL\ F\ []$
apply (*rule exprel.intros*)
apply (*rule listrel.intros*)
done

lemma *FNCALL-Cons*:
$[\![X \sim X';\ (Xs,Xs') \in listrel(exprel)]\!]$
$\Longrightarrow FNCALL\ F\ (X\#Xs) \sim FNCALL\ F\ (X'\#Xs')$
by (*blast intro*: *exprel.intros listrel.intros*)

4.2 Some Functions on the Free Algebra

4.2.1 The Set of Variables

A function to return the set of variables present in a message. It will be lifted to the initial algebra, to serve as an example of that process. Note that the "free" refers to the free datatype rather than to the concept of a free variable.

primrec *freevars* :: *freeExp* ⇒ *nat set*
and *freevars-list* :: *freeExp list* ⇒ *nat set* **where**

freevars (*VAR N*) = {*N*}
| *freevars* (*PLUS X Y*) = *freevars X* ∪ *freevars Y*
| *freevars* (*FNCALL F Xs*) = *freevars-list Xs*

| *freevars-list* [] = {}
| *freevars-list* (*X* # *Xs*) = *freevars X* ∪ *freevars-list Xs*

This theorem lets us prove that the vars function respects the equivalence relation. It also helps us prove that Variable (the abstract constructor) is injective

theorem *exprel-imp-eq-freevars*: *U* ∼ *V* ⟹ *freevars U* = *freevars V*
apply (*induct set*: *exprel*)
apply (*erule-tac* [*4*] *listrel.induct*)
apply (*simp-all add*: *Un-assoc*)
done

4.2.2 Functions for Freeness

A discriminator function to distinguish vars, sums and function calls

primrec *freediscrim* :: *freeExp* ⇒ *int* **where**
freediscrim (*VAR N*) = *0*
| *freediscrim* (*PLUS X Y*) = *1*
| *freediscrim* (*FNCALL F Xs*) = *2*

theorem *exprel-imp-eq-freediscrim*:
U ∼ *V* ⟹ *freediscrim U* = *freediscrim V*
by (*induct set*: *exprel*) *auto*

This function, which returns the function name, is used to prove part of the injectivity property for FnCall.

primrec *freefun* :: *freeExp* ⇒ *nat* **where**
freefun (*VAR N*) = *0*
| *freefun* (*PLUS X Y*) = *0*
| *freefun* (*FNCALL F Xs*) = *F*

theorem *exprel-imp-eq-freefun*:
U ∼ *V* ⟹ *freefun U* = *freefun V*
by (*induct set*: *exprel*) (*simp-all add*: *listrel.intros*)

This function, which returns the list of function arguments, is used to prove part of the injectivity property for FnCall.

primrec *freeargs* :: *freeExp* ⇒ *freeExp list* **where**
freeargs (*VAR N*) = []
| *freeargs* (*PLUS X Y*) = []
| *freeargs* (*FNCALL F Xs*) = *Xs*

theorem *exprel-imp-eqv-freeargs*:

assumes $U \sim V$
shows (*freeargs* U, *freeargs* V) $\in$ *listrel exprel*
proof −
from *equiv-list-exprel* **have** *sym*: *sym* (*listrel exprel*) **by** (*rule equivE*)
from *equiv-list-exprel* **have** *trans*: *trans* (*listrel exprel*) **by** (*rule equivE*)
from *assms* **show** *?thesis*
apply *induct*
apply (*erule-tac* [*4*] *listrel.induct*)
apply (*simp-all add*: *listrel.intros*)
apply (*blast intro*: *symD* [*OF sym*])
apply (*blast intro*: *transD* [*OF trans*])
done
qed

4.3 The Initial Algebra: A Quotiented Message Type

definition *Exp* = *UNIV*//*exprel*

typedef *exp* = *Exp*
morphisms *Rep-Exp Abs-Exp*
unfolding *Exp-def* **by** (*auto simp add*: *quotient-def*)

The abstract message constructors

definition
Var :: *nat* ⇒ *exp* **where**
Var N = *Abs-Exp*(*exprel*``{*VAR N*})

definition
Plus :: [*exp*,*exp*] ⇒ *exp* **where**
Plus X Y =
Abs-Exp (⋃ *U* ∈ *Rep-Exp X*. ⋃ *V* ∈ *Rep-Exp Y*. *exprel*``{*PLUS U V*})

definition
FnCall :: [*nat*, *exp list*] ⇒ *exp* **where**
FnCall F Xs =
Abs-Exp (⋃ *Us* ∈ *listset* (*map Rep-Exp Xs*). *exprel* `` {*FNCALL F Us*})

Reduces equality of equivalence classes to the *exprel* relation: (*exprel* `` {$x$} = *exprel* `` {y}) = ($x \sim y$)

lemmas *equiv-exprel-iff* = *eq-equiv-class-iff* [*OF equiv-exprel UNIV-I UNIV-I*]

declare *equiv-exprel-iff* [*simp*]

All equivalence classes belong to set of representatives

lemma [*simp*]: *exprel*``{*U*} ∈ *Exp*
by (*auto simp add*: *Exp-def quotient-def intro*: *exprel-refl*)

lemma *inj-on-Abs-Exp*: *inj-on Abs-Exp Exp*
apply (*rule inj-on-inverseI*)

apply (*erule Abs-Exp-inverse*)
done

Reduces equality on abstractions to equality on representatives

declare *inj-on-Abs-Exp* [*THEN inj-on-eq-iff*, *simp*]

declare *Abs-Exp-inverse* [*simp*]

Case analysis on the representation of a exp as an equivalence class.

lemma *eq-Abs-Exp* [*case-names Abs-Exp*, *cases type*: *exp*]:
  (!!*U*. *z* = *Abs-Exp*(*exprel*``{*U*}) ==> *P*) ==> *P*
apply (*rule Rep-Exp* [*of z*, *unfolded Exp-def*, *THEN quotientE*])
apply (*drule arg-cong* [**where** *f*=*Abs-Exp*])
apply (*auto simp add*: *Rep-Exp-inverse intro*: *exprel-refl*)
done

4.4 Every list of abstract expressions can be expressed in terms of a list of concrete expressions

definition
  Abs-ExpList :: *freeExp list* => *exp list* **where**
  Abs-ExpList Xs = *map* (%*U*. *Abs-Exp*(*exprel*``{*U*})) *Xs*

lemma *Abs-ExpList-Nil* [*simp*]: *Abs-ExpList* [] == []
by (*simp add*: *Abs-ExpList-def*)

lemma *Abs-ExpList-Cons* [*simp*]:
  Abs-ExpList (*X*#*Xs*) == *Abs-Exp* (*exprel*``{*X*}) # *Abs-ExpList Xs*
by (*simp add*: *Abs-ExpList-def*)

lemma *ExpList-rep*: ∃ *Us*. *z* = *Abs-ExpList Us*
apply (*induct z*)
apply (*rename-tac* [*2*] *a b*)
apply (*rule-tac* [*2*] *z*=*a* **in** *eq-Abs-Exp*)
apply (*auto simp add*: *Abs-ExpList-def Cons-eq-map-conv intro*: *exprel-refl*)
done

lemma *eq-Abs-ExpList* [*case-names Abs-ExpList*]:
  (!!*Us*. *z* = *Abs-ExpList Us* ==> *P*) ==> *P*
by (*rule exE* [*OF ExpList-rep*], *blast*)

4.4.1 Characteristic Equations for the Abstract Constructors

lemma *Plus*: *Plus* (*Abs-Exp*(*exprel*``{*U*})) (*Abs-Exp*(*exprel*``{*V*})) =
    Abs-Exp (*exprel*``{*PLUS U V*})
proof −
  have (λ*U V*. *exprel* `` {*PLUS U V*}) *respects2 exprel*
    by (*auto simp add*: *congruent2-def exprel.PLUS*)
  thus *?thesis*

by (*simp add*: *Plus-def UN-equiv-class2* [*OF equiv-exprel equiv-exprel*])
qed

It is not clear what to do with FnCall: it's argument is an abstraction of an *exp list*. Is it just Nil or Cons? What seems to work best is to regard an *exp list* as a *listrel exprel* equivalence class

This theorem is easily proved but never used. There's no obvious way even to state the analogous result, *FnCall-Cons*.

lemma *FnCall-Nil*: *FnCall F* [] = *Abs-Exp* (*exprel*``{*FNCALL F* []})
by (*simp add*: *FnCall-def*)

lemma *FnCall-respects*:
(λ*Us*. *exprel* `` {*FNCALL F Us*}) *respects* (*listrel exprel*)
by (*auto simp add*: *congruent-def exprel.FNCALL*)

lemma *FnCall-sing*:
FnCall F [*Abs-Exp*(*exprel*``{*U*})] = *Abs-Exp* (*exprel*``{*FNCALL F* [*U*]})
proof −
have (λ*U*. *exprel* `` {*FNCALL F* [*U*]}) *respects exprel*
by (*auto simp add*: *congruent-def FNCALL-Cons listrel.intros*)
thus *?thesis*
by (*simp add*: *FnCall-def UN-equiv-class* [*OF equiv-exprel*])
qed

lemma *listset-Rep-Exp-Abs-Exp*:
listset (*map Rep-Exp* (*Abs-ExpList Us*)) = *listrel exprel* `` {*Us*}
by (*induct Us*) (*simp-all add*: *listrel-Cons Abs-ExpList-def*)

lemma *FnCall*:
FnCall F (*Abs-ExpList Us*) = *Abs-Exp* (*exprel*``{*FNCALL F Us*})
proof −
have (λ*Us*. *exprel* `` {*FNCALL F Us*}) *respects* (*listrel exprel*)
by (*auto simp add*: *congruent-def exprel.FNCALL*)
thus *?thesis*
by (*simp add*: *FnCall-def UN-equiv-class* [*OF equiv-list-exprel*]
listset-Rep-Exp-Abs-Exp)
qed

Establishing this equation is the point of the whole exercise

theorem *Plus-assoc*: *Plus X* (*Plus Y Z*) = *Plus* (*Plus X Y*) *Z*
by (*cases X*, *cases Y*, *cases Z*, *simp add*: *Plus exprel.ASSOC*)

4.5 The Abstract Function to Return the Set of Variables

definition
vars :: *exp* ⇒ *nat set* **where**
vars X = (⋃ *U* ∈ *Rep-Exp X*. *freevars U*)

lemma *vars-respects*: *freevars respects exprel*
by (*auto simp add*: *congruent-def exprel-imp-eq-freevars*)

The extension of the function *vars* to lists

primrec *vars-list* :: *exp list* ⇒ *nat set* **where**
  vars-list [] = {}
| *vars-list*(*E*#*Es*) = *vars E* ∪ *vars-list Es*

Now prove the three equations for *vars*

lemma *vars-Variable* [*simp*]: *vars* (*Var N*) = {*N*}
by (*simp add*: *vars-def Var-def*
  UN-equiv-class [*OF equiv-exprel vars-respects*])

lemma *vars-Plus* [*simp*]: *vars* (*Plus X Y*) = *vars X* ∪ *vars Y*
apply (*cases X*, *cases Y*)
apply (*simp add*: *vars-def Plus*
  UN-equiv-class [*OF equiv-exprel vars-respects*])
done

lemma *vars-FnCall* [*simp*]: *vars* (*FnCall F Xs*) = *vars-list Xs*
apply (*cases Xs rule*: *eq-Abs-ExpList*)
apply (*simp add*: *FnCall*)
apply (*induct-tac Us*)
apply (*simp-all add*: *vars-def UN-equiv-class* [*OF equiv-exprel vars-respects*])
done

lemma *vars-FnCall-Nil*: *vars* (*FnCall F Nil*) = {}
by *simp*

lemma *vars-FnCall-Cons*: *vars* (*FnCall F* (*X*#*Xs*)) = *vars X* ∪ *vars-list Xs*
by *simp*

4.6 Injectivity Properties of Some Constructors

lemma *VAR-imp-eq*: *VAR m* ∼ *VAR n* ⟹ *m* = *n*
by (*drule exprel-imp-eq-freevars*, *simp*)

Can also be proved using the function *vars*

lemma *Var-Var-eq* [*iff*]: (*Var m* = *Var n*) = (*m* = *n*)
by (*auto simp add*: *Var-def exprel-refl dest*: *VAR-imp-eq*)

lemma *VAR-neqv-PLUS*: *VAR m* ∼ *PLUS X Y* ⟹ *False*
by (*drule exprel-imp-eq-freediscrim*, *simp*)

theorem *Var-neq-Plus* [*iff*]: *Var N* ≠ *Plus X Y*
apply (*cases X*, *cases Y*)
apply (*simp add*: *Var-def Plus*)
apply (*blast dest*: *VAR-neqv-PLUS*)
done

theorem *Var-neq-FnCall* [*iff*]: *Var N* $\neq$ *FnCall F Xs*
apply (*cases Xs rule*: *eq-Abs-ExpList*)
apply (*auto simp add*: *FnCall Var-def*)
apply (*drule exprel-imp-eq-freediscrim*, *simp*)
done

4.7 Injectivity of *FnCall*

definition
fun :: *exp* $\Rightarrow$ *nat* **where**
fun X = *the-elem* ($\bigcup$ *U* $\in$ *Rep-Exp X*. {*freefun U*})

lemma *fun-respects*: (%*U*. {*freefun U*}) *respects exprel*
by (*auto simp add*: *congruent-def exprel-imp-eq-freefun*)

lemma *fun-FnCall* [*simp*]: *fun* (*FnCall F Xs*) = *F*
apply (*cases Xs rule*: *eq-Abs-ExpList*)
apply (*simp add*: *FnCall fun-def UN-equiv-class* [*OF equiv-exprel fun-respects*])
done

definition
args :: *exp* $\Rightarrow$ *exp list* **where**
args X = *the-elem* ($\bigcup$ *U* $\in$ *Rep-Exp X*. {*Abs-ExpList* (*freeargs U*)})

This result can probably be generalized to arbitrary equivalence relations, but with little benefit here.

lemma *Abs-ExpList-eq*:
(*y*, *z*) $\in$ *listrel exprel* $\Longrightarrow$ *Abs-ExpList* (*y*) = *Abs-ExpList* (*z*)
by (*induct set*: *listrel*) *simp-all*

lemma *args-respects*: (%*U*. {*Abs-ExpList* (*freeargs U*)}) *respects exprel*
by (*auto simp add*: *congruent-def Abs-ExpList-eq exprel-imp-eqv-freeargs*)

lemma *args-FnCall* [*simp*]: *args* (*FnCall F Xs*) = *Xs*
apply (*cases Xs rule*: *eq-Abs-ExpList*)
apply (*simp add*: *FnCall args-def UN-equiv-class* [*OF equiv-exprel args-respects*])
done

lemma *FnCall-FnCall-eq* [*iff*]:
(*FnCall F Xs* = *FnCall F′ Xs′*) = (*F*=*F′* & *Xs*=*Xs′*)
proof
assume *FnCall F Xs* = *FnCall F′ Xs′*
hence *fun* (*FnCall F Xs*) = *fun* (*FnCall F′ Xs′*)
and *args* (*FnCall F Xs*) = *args* (*FnCall F′ Xs′*) **by** *auto*
thus *F*=*F′* & *Xs*=*Xs′* **by** *simp*
next
assume *F*=*F′* & *Xs*=*Xs′* **thus** *FnCall F Xs* = *FnCall F′ Xs′* **by** *simp*

qed

4.8 The Abstract Discriminator

However, as *FnCall-Var-neq-Var* illustrates, we don't need this function in order to prove discrimination theorems.

definition
discrim :: *exp* ⇒ *int* **where**
discrim X = *the-elem* (⋃ *U* ∈ *Rep-Exp X*. {*freediscrim U*})

lemma *discrim-respects*: (λ*U*. {*freediscrim U*}) *respects exprel*
by (*auto simp add*: *congruent-def exprel-imp-eq-freediscrim*)

Now prove the four equations for *discrim*

lemma *discrim-Var* [*simp*]: *discrim* (*Var N*) = *0*
by (*simp add*: *discrim-def Var-def*
UN-equiv-class [*OF equiv-exprel discrim-respects*])

lemma *discrim-Plus* [*simp*]: *discrim* (*Plus X Y*) = *1*
apply (*cases X*, *cases Y*)
apply (*simp add*: *discrim-def Plus*
UN-equiv-class [*OF equiv-exprel discrim-respects*])
done

lemma *discrim-FnCall* [*simp*]: *discrim* (*FnCall F Xs*) = *2*
apply (*rule-tac z=Xs* **in** *eq-Abs-ExpList*)
apply (*simp add*: *discrim-def FnCall*
UN-equiv-class [*OF equiv-exprel discrim-respects*])
done

The structural induction rule for the abstract type

theorem *exp-inducts*:
assumes *V*: ⋀*nat*. *P1* (*Var nat*)
and *P*: ⋀*exp1 exp2*. ⟦*P1 exp1*; *P1 exp2*⟧ ⟹ *P1* (*Plus exp1 exp2*)
and *F*: ⋀*nat list*. *P2 list* ⟹ *P1* (*FnCall nat list*)
and *Nil*: *P2* []
and *Cons*: ⋀*exp list*. ⟦*P1 exp*; *P2 list*⟧ ⟹ *P2* (*exp* # *list*)
shows *P1 exp* **and** *P2 list*
proof −
obtain *U* **where** *exp*: *exp* = (*Abs-Exp* (*exprel* `` {*U*})) **by** (*cases exp*)
obtain *Us* **where** *list*: *list* = *Abs-ExpList Us* **by** (*rule eq-Abs-ExpList*)
have *P1* (*Abs-Exp* (*exprel* `` {*U*})) **and** *P2* (*Abs-ExpList Us*)
proof (*induct U* **and** *Us rule*: *compat-freeExp.induct compat-freeExp-list.induct*)
case (*VAR nat*)
with *V* **show** *?case* **by** (*simp add*: *Var-def*)
next
case (*PLUS X Y*)
with *P* [*of Abs-Exp* (*exprel* `` {*X*}) *Abs-Exp* (*exprel* `` {*Y*})]

```
    show ?case by (simp add: Plus)
  next
    case (FNCALL nat list)
    with F [of Abs-ExpList list]
    show ?case by (simp add: FnCall)
  next
    case Nil-freeExp
    with Nil show ?case by simp
  next
    case Cons-freeExp
    with Cons show ?case by simp
  qed
  with exp and list show P1 exp and P2 list by (simp-all only:)
qed

end
```

5 Terms over a given alphabet

```
theory Term
imports Main
begin

datatype ('a, 'b) term =
    Var 'a
  | App 'b ('a, 'b) term list
```

Substitution function on terms

```
primrec subst-term :: ('a ⇒ ('a, 'b) term) ⇒ ('a, 'b) term ⇒ ('a, 'b) term
  and subst-term-list :: ('a ⇒ ('a, 'b) term) ⇒ ('a, 'b) term list ⇒ ('a, 'b) term
list
where
  subst-term f (Var a) = f a
| subst-term f (App b ts) = App b (subst-term-list f ts)
| subst-term-list f [] = []
| subst-term-list f (t # ts) = subst-term f t # subst-term-list f ts
```

A simple theorem about composition of substitutions

```
lemma subst-comp:
  subst-term (subst-term f1 ∘ f2) t =
    subst-term f1 (subst-term f2 t)
and subst-term-list (subst-term f1 ∘ f2) ts =
    subst-term-list f1 (subst-term-list f2 ts)
  by (induct t and ts rule: subst-term.induct subst-term-list.induct) simp-all
```

Alternative induction rule

```
lemma
```

```
  assumes var: ⋀v. P (Var v)
    and app: ⋀f ts. (∀ t ∈ set ts. P t) ⟹ P (App f ts)
  shows term-induct2: P t
    and ∀ t ∈ set ts. P t
  apply (induct t and ts rule: subst-term.induct subst-term-list.induct)
     apply (rule var)
    apply (rule app)
    apply assumption
   apply simp-all
  done

end


theory Sexp
imports HOL−Library.Old-Datatype
begin

type-synonym 'a item = 'a Old-Datatype.item
abbreviation Leaf == Old-Datatype.Leaf
abbreviation Numb == Old-Datatype.Numb

inductive-set
  sexp      :: 'a item set
  where
    LeafI:  Leaf(a) ∈ sexp
  | NumbI:  Numb(i) ∈ sexp
  | SconsI: [| M ∈ sexp;  N ∈ sexp |] ==> Scons M N ∈ sexp

definition
  sexp-case :: ['a=>'b, nat=>'b, ['a item, 'a item]=>'b,
                'a item] => 'b where
  sexp-case c d e M = (THE z. (∃ x.    M=Leaf(x) & z=c(x))
                            | (∃ k.    M=Numb(k) & z=d(k))
                            | (∃ N1 N2. M = Scons N1 N2  & z=e N1 N2))

definition
  pred-sexp :: ('a item ∗ 'a item)set where
     pred-sexp = (⋃ M ∈ sexp. ⋃ N ∈ sexp. {(M, Scons M N), (N, Scons M N)})

definition
  sexp-rec  :: ['a item, 'a=>'b, nat=>'b,
                ['a item, 'a item, 'b, 'b]=>'b] => 'b where
   sexp-rec M c d e = wfrec pred-sexp
            (%g. sexp-case c d (%N1 N2. e N1 N2 (g N1) (g N2))) M
```

lemma *sexp-case-Leaf* [*simp*]: *sexp-case c d e* (*Leaf a*) = *c*(*a*)
by (*simp add*: *sexp-case-def*, *blast*)

lemma *sexp-case-Numb* [*simp*]: *sexp-case c d e* (*Numb k*) = *d*(*k*)
by (*simp add*: *sexp-case-def*, *blast*)

lemma *sexp-case-Scons* [*simp*]: *sexp-case c d e* (*Scons M N*) = *e M N*
by (*simp add*: *sexp-case-def*)

lemma *sexp-In0I*: *M* ∈ *sexp* ==> *In0*(*M*) ∈ *sexp*
apply (*simp add*: *In0-def*)
apply (*erule sexp.NumbI* [*THEN sexp.ConsI*])
done

lemma *sexp-In1I*: *M* ∈ *sexp* ==> *In1*(*M*) ∈ *sexp*
apply (*simp add*: *In1-def*)
apply (*erule sexp.NumbI* [*THEN sexp.ConsI*])
done

declare *sexp.intros* [*intro*,*simp*]

lemma *range-Leaf-subset-sexp*: *range*(*Leaf*) <= *sexp*
by *blast*

lemma *Cons-D*: *Cons M N* ∈ *sexp* ==> *M* ∈ *sexp* & *N* ∈ *sexp*
by (*induct S* == *Cons M N set*: *sexp*) *auto*

lemma *pred-sexp-subset-Sigma*: *pred-sexp* <= *sexp* × *sexp*
by (*simp add*: *pred-sexp-def*) *blast*

lemmas *trancl-pred-sexpD1* =
pred-sexp-subset-Sigma
[*THEN trancl-subset-Sigma*, *THEN subsetD*, *THEN SigmaD1*]
and *trancl-pred-sexpD2* =
pred-sexp-subset-Sigma
[*THEN trancl-subset-Sigma*, *THEN subsetD*, *THEN SigmaD2*]

lemma *pred-sexpI1*:
[| *M* ∈ *sexp*; *N* ∈ *sexp* |] ==> (*M*, *Cons M N*) ∈ *pred-sexp*
by (*simp add*: *pred-sexp-def*, *blast*)

lemma *pred-sexpI2*:

[| $M \in sexp$; $N \in sexp$ |] ==> $(N, Scons\ M\ N) \in pred\text{-}sexp$
by (*simp add*: *pred-sexp-def*, *blast*)

lemmas *pred-sexp-t1* [*simp*] = *pred-sexpI1* [*THEN r-into-trancl*]
and *pred-sexp-t2* [*simp*] = *pred-sexpI2* [*THEN r-into-trancl*]

lemmas *pred-sexp-trans1* [*simp*] = *trans-trancl* [*THEN transD*, *OF - pred-sexp-t1*]
and *pred-sexp-trans2* [*simp*] = *trans-trancl* [*THEN transD*, *OF - pred-sexp-t2*]

declare *cut-apply* [*simp*]

lemma *pred-sexpE*:
[| $p \in pred\text{-}sexp$;
!!$M\ N$. [| $p = (M, Scons\ M\ N)$; $M \in sexp$; $N \in sexp$ |] ==> R;
!!$M\ N$. [| $p = (N, Scons\ M\ N)$; $M \in sexp$; $N \in sexp$ |] ==> R
|] ==> R
by (*simp add*: *pred-sexp-def*, *blast*)

lemma *wf-pred-sexp*: *wf*(*pred-sexp*)
apply (*rule pred-sexp-subset-Sigma* [*THEN wfI*])
apply (*erule sexp.induct*)
apply (*blast elim*!: *pred-sexpE*)+
done

lemma *sexp-rec-unfold-lemma*:
(%M. *sexp-rec* $M\ c\ d\ e$) ==
wfrec pred-sexp (%g. *sexp-case* $c\ d$ (%$N1\ N2$. $e\ N1\ N2\ (g\ N1)\ (g\ N2)$))
by (*simp add*: *sexp-rec-def*)

lemmas *sexp-rec-unfold* = *def-wfrec* [*OF sexp-rec-unfold-lemma wf-pred-sexp*]

lemma *sexp-rec-Leaf*: *sexp-rec* (*Leaf* a) $c\ d\ h = c(a)$
apply (*subst sexp-rec-unfold*)
apply (*rule sexp-case-Leaf*)
done

lemma *sexp-rec-Numb*: *sexp-rec* (*Numb* k) $c\ d\ h = d(k)$
apply (*subst sexp-rec-unfold*)
apply (*rule sexp-case-Numb*)
done

lemma *sexp-rec-Scons*: [| $M \in sexp$; $N \in sexp$ |] ==>
  sexp-rec (*Scons M N*) *c d h* = *h M N* (*sexp-rec M c d h*) (*sexp-rec N c d h*)
apply (*rule sexp-rec-unfold* [*THEN trans*])
apply (*simp add*: *pred-sexpI1 pred-sexpI2*)
done

end

6 Extended List Theory (old)

theory *SList*
imports *Sexp*
begin

definition
  NIL :: *'a item* **where**
  NIL = *In0*(*Numb*(*0*))

definition
  CONS :: [*'a item*, *'a item*] => *'a item* **where**
  CONS M N = *In1*(*Scons M N*)

inductive-set
  list :: *'a item set* => *'a item set*
  for *A* :: *'a item set*
  where
    NIL-I: *NIL* ∈ *list A*
  | *CONS-I*: [| $a \in A$; $M \in$ *list A* |] ==> *CONS a M* ∈ *list A*

definition *List* = *list* (*range Leaf*)

typedef *'a list* = *List* :: *'a item set*
  morphisms *Rep-List Abs-List*
  unfolding *List-def* **by** (*blast intro*: *list.NIL-I*)

abbreviation *Case* == *Old-Datatype.Case*
abbreviation *Split* == *Old-Datatype.Split*

definition
List-case :: ['b, ['a item, 'a item]=>'b, 'a item] => 'b **where**
List-case c d = *Case*(%*x*. *c*)(*Split*(*d*))

definition
List-rec :: ['a item, 'b, ['a item, 'a item, 'b]=>'b] => 'b **where**
List-rec M c d = *wfrec* (*pred-sexp*$^+$)
(%*g*. *List-case c* (%*x y*. *d x y* (*g y*))) *M*

no-translations
[*x*, *xs*] == *x*#[*xs*]
[*x*] == *x*#[]
no-notation
Nil ([]) **and**
Cons (**infixr** # *65*)

definition
Nil :: 'a list ([]) **where**
Nil = *Abs-List*(*NIL*)

definition
Cons :: ['a, 'a list] => 'a list (**infixr** # *65*) **where**
x#*xs* = *Abs-List*(*CONS* (*Leaf x*)(*Rep-List xs*))

definition

list-rec :: ['a list, 'b, ['a, 'a list, 'b]=>'b] => 'b **where**
list-rec l c d =
List-rec(*Rep-List l*) *c* (%*x y r*. *d*(*inv Leaf x*)(*Abs-List y*) *r*)

definition
list-case :: ['b, ['a, 'a list]=>'b, 'a list] => 'b **where**
list-case a f xs = *list-rec xs a* (%*x xs r*. *f x xs*)

translations
[*x*, *xs*] == *x*#[*xs*]
[*x*] == *x*#[]

case xs of [] => *a* | *y*#*ys* => *b* == *CONST list-case*(*a*, %*y ys*. *b*, *xs*)

definition
Rep-map :: ('*b* => '*a item*) => ('*b list* => '*a item*) **where**
Rep-map f xs = *list-rec xs* *NIL*(%*x l r*. *CONS*(*f x*) *r*)

definition
Abs-map :: ('*a item* => '*b*) => '*a item* => '*b list* **where**
Abs-map g M = *List-rec M Nil* (%*N L r*. *g*(*N*)#*r*)

definition
map :: ('*a*=>'*b*) => ('*a list* => '*b list*) **where**
map f xs = *list-rec xs* [] (%*x l r*. *f*(*x*)#*r*)

primrec *take* :: ['*a list*,*nat*] => '*a list* **where**
take-0: *take xs 0* = []
| *take-Suc*: *take xs* (*Suc n*) = *list-case* [] (%*x l*. *x* # *take l n*) *xs*

lemma *ListI*: *x* ∈ *list* (*range Leaf*) ⟹ *x* ∈ *List*
by (*simp add*: *List-def*)

lemma *ListD*: *x* ∈ *List* ⟹ *x* ∈ *list* (*range Leaf*)
by (*simp add*: *List-def*)

lemma *list-unfold*: *list*(*A*) = *usum* {*Numb*(*0*)} (*uprod A* (*list*(*A*)))
by (*fast intro*!: *list.intros* [*unfolded NIL-def CONS-def*]
elim: *list.cases* [*unfolded NIL-def CONS-def*])

lemma *list-mono*: *A*<=*B* ==> *list*(*A*) <= *list*(*B*)
apply (*rule subsetI*)
apply (*erule list.induct*)
apply (*auto intro*!: *list.intros*)
done

lemma *list-sexp*: *list*(*sexp*) <= *sexp*
apply (*rule subsetI*)

apply (*erule list.induct*)
apply (*unfold NIL-def CONS-def*)
apply (*auto intro*: *sexp.intros sexp-In0I sexp-In1I*)
done

lemmas *list-subset-sexp* = *subset-trans* [*OF list-mono list-sexp*]

lemma *list-induct*:
  [| *P*(*Nil*);
    !!*x xs*. *P*(*xs*) ==> *P*(*x* # *xs*) |] ==> *P*(*l*)
apply (*unfold Nil-def Cons-def*)
apply (*rule Rep-List-inverse* [*THEN subst*])

apply (*rule Rep-List* [*unfolded List-def*, *THEN list.induct*], *simp*)
apply (*erule Abs-List-inverse* [*unfolded List-def*, *THEN subst*], *blast*)
done

lemma *inj-on-Abs-list*: *inj-on Abs-List* (*list*(*range Leaf*))
apply (*rule inj-on-inverseI*)
apply (*erule Abs-List-inverse* [*unfolded List-def*])
done

lemma *CONS-not-NIL* [*iff*]: *CONS M N* ~= *NIL*
by (*simp add*: *NIL-def CONS-def*)

lemmas *NIL-not-CONS* [*iff*] = *CONS-not-NIL* [*THEN not-sym*]
lemmas *CONS-neq-NIL* = *CONS-not-NIL* [*THEN notE*]
lemmas *NIL-neq-CONS* = *sym* [*THEN CONS-neq-NIL*]

lemma *Cons-not-Nil* [*iff*]: *x* # *xs* ~= *Nil*
apply (*unfold Nil-def Cons-def*)
apply (*rule CONS-not-NIL* [*THEN inj-on-Abs-list* [*THEN inj-on-contraD*]])
apply (*simp-all add*: *list.intros rangeI Rep-List* [*unfolded List-def*])
done

lemmas *Nil-not-Cons* = *Cons-not-Nil* [*THEN not-sym*]
declare *Nil-not-Cons* [*iff*]
lemmas *Cons-neq-Nil* = *Cons-not-Nil* [*THEN notE*]
lemmas *Nil-neq-Cons* = *sym* [*THEN Cons-neq-Nil*]

lemma *CONS-CONS-eq* [*iff*]: (*CONS K M*)=(*CONS L N*) = (*K*=*L* & *M*=*N*)
by (*simp add*: *CONS-def*)

declare *Rep-List* [*THEN ListD*, *intro*] *ListI* [*intro*]
declare *list.intros* [*intro*,*simp*]
declare *Leaf-inject* [*dest*!]

lemma *Cons-Cons-eq* [*iff*]: (*x*#*xs*=*y*#*ys*) = (*x*=*y* & *xs*=*ys*)
apply (*simp add*: *Cons-def*)
apply (*subst Abs-List-inject*)
apply (*auto simp add*: *Rep-List-inject*)
done

lemmas *Cons-inject2* = *Cons-Cons-eq* [*THEN iffD1*, *THEN conjE*]

lemma *CONS-D*: *CONS M N* ∈ *list*(*A*) ⟹ *M* ∈ *A* & *N* ∈ *list*(*A*)
by (*induct L* == *CONS M N rule*: *list.induct*) *auto*

lemma *sexp-CONS-D*: *CONS M N* ∈ *sexp* ⟹ *M* ∈ *sexp* ∧ *N* ∈ *sexp*
apply (*simp add*: *CONS-def In1-def*)
apply (*fast dest*!: *Scons-D*)
done

lemma *not-CONS-self*: *N* ∈ *list*(*A*) ⟹ ∀ *M*. *N* ≠ *CONS M N*
apply (*erule list.induct*) **apply** *simp-all* **done**

lemma *not-Cons-self2*: ∀ *x*. *l* ≠ *x*#*l*
by (*induct l rule*: *list-induct*) *simp-all*

lemma *neq-Nil-conv2*: (*xs* ≠ []) = (∃ *y ys*. *xs* = *y*#*ys*)
by (*induct xs rule*: *list-induct*) *auto*

lemma *List-case-NIL* [*simp*]: *List-case c h NIL* = *c*
by (*simp add*: *List-case-def NIL-def*)

lemma *List-case-CONS* [*simp*]: *List-case c h* (*CONS M N*) = *h M N*
by (*simp add*: *List-case-def CONS-def*)

lemma *List-rec-unfold-lemma*:
$(\lambda M.\ List\text{-}rec\ M\ c\ d) \equiv$
$wfrec\ (pred\text{-}sexp^{+})\ (\lambda g.\ List\text{-}case\ c\ (\lambda x\ y.\ d\ x\ y\ (g\ y)))$
by (*simp add*: *List-rec-def*)

lemmas *List-rec-unfold* =
def-wfrec [*OF List-rec-unfold-lemma wf-pred-sexp* [*THEN wf-trancl*]]

lemma *pred-sexp-CONS-I1*:
$[|\ M \in sexp;\ \ N \in sexp\ |] ==> (M,\ CONS\ M\ N) \in pred\text{-}sexp^{+}$
by (*simp add*: *CONS-def In1-def*)

lemma *pred-sexp-CONS-I2*:
$[|\ M \in sexp;\ \ N \in sexp\ |] ==> (N,\ CONS\ M\ N) \in pred\text{-}sexp^{+}$
by (*simp add*: *CONS-def In1-def*)

lemma *pred-sexp-CONS-D*:
$(CONS\ M1\ M2,\ N) \in pred\text{-}sexp^{+} \Longrightarrow$
$(M1,N) \in pred\text{-}sexp^{+} \wedge (M2,N) \in pred\text{-}sexp^{+}$
apply (*frule pred-sexp-subset-Sigma* [*THEN trancl-subset-Sigma*, *THEN subsetD*])
apply (*blast dest*!: *sexp-CONS-D intro*: *pred-sexp-CONS-I1 pred-sexp-CONS-I2*
trans-trancl [*THEN transD*])
done

lemma *List-rec-NIL* [*simp*]: $List\text{-}rec\ NIL\ c\ h = c$
apply (*rule List-rec-unfold* [*THEN trans*])
apply (*simp add*: *List-case-NIL*)
done

lemma *List-rec-CONS* [*simp*]:
$[|\ M \in sexp;\ \ N \in sexp\ |]$
$==> List\text{-}rec\ (CONS\ M\ N)\ c\ h = h\ M\ N\ (List\text{-}rec\ N\ c\ h)$
apply (*rule List-rec-unfold* [*THEN trans*])
apply (*simp add*: *pred-sexp-CONS-I2*)
done

lemmas *Rep-List-in-sexp* =

subsetD [*OF range-Leaf-subset-sexp* [*THEN list-subset-sexp*]
Rep-List [*THEN ListD*]]

lemma *list-rec-Nil* [*simp*]: *list-rec Nil c h* = *c*
by (*simp add*: *list-rec-def ListI* [*THEN Abs-List-inverse*] *Nil-def*)

lemma *list-rec-Cons* [*simp*]: *list-rec* (*a*#*l*) *c h* = *h a l* (*list-rec l c h*)
by (*simp add*: *list-rec-def ListI* [*THEN Abs-List-inverse*] *Cons-def*
Rep-List-inverse Rep-List [*THEN ListD*] *inj-Leaf Rep-List-in-sexp*)

lemma *List-rec-type*:
[| $M \in list(A)$;
A<=*sexp*;
$c \in C(NIL)$;
$\bigwedge x\ y\ r.$ [| $x \in A$; $y \in list(A)$; $r \in C(y)$ |] ==> $h\ x\ y\ r \in C(CONS\ x\ y)$
|] ==> *List-rec* $M\ c\ h \in C(M :: 'a\ item)$
apply (*erule list.induct*, *simp*)
apply (*insert list-subset-sexp*)
apply (*subst List-rec-CONS*, *blast*+)
done

lemma *Rep-map-Nil* [*simp*]: *Rep-map f Nil* = *NIL*
by (*simp add*: *Rep-map-def*)

lemma *Rep-map-Cons* [*simp*]:
Rep-map f(*x*#*xs*) = *CONS*(*f x*)(*Rep-map f xs*)
by (*simp add*: *Rep-map-def*)

lemma *Rep-map-type*: $(\bigwedge x.\ f(x) \in A) \Longrightarrow$ *Rep-map f xs* $\in list(A)$
apply (*simp add*: *Rep-map-def*)
apply (*rule list-induct*, *auto*)
done

lemma *Abs-map-NIL* [*simp*]: *Abs-map g NIL* = *Nil*
by (*simp add*: *Abs-map-def*)

lemma *Abs-map-CONS* [*simp*]:
[| $M \in sexp$; $N \in sexp$ |] ==> *Abs-map g* (*CONS M N*) = $g(M)$ # *Abs-map g N*
by (*simp add*: *Abs-map-def*)

lemma *def-list-rec-NilCons*:
$[\![\bigwedge xs.\ f(xs) = \textit{list-rec}\ xs\ c\ h\ ]\!]$
$\Longrightarrow f\ [] = c \wedge f(x\#xs) = h\ x\ xs\ (f\ xs)$
by *simp*

lemma *Abs-map-inverse*:
$[\![M \in \textit{list}(A);\ \ A{<}{=}\textit{sexp};\ \ \bigwedge z.\ z \in A \Longrightarrow f(g(z)) = z\ ]\!]$
$\Longrightarrow \textit{Rep-map}\ f\ (\textit{Abs-map}\ g\ M) = M$
apply (*erule list.induct*, *simp-all*)
apply (*insert list-subset-sexp*)
apply (*subst Abs-map-CONS*, *blast*)
apply *blast*
apply *simp*
done

Better to have a single theorem with a conjunctive conclusion.

declare *def-list-rec-NilCons* [*OF list-case-def*, *simp*]

lemma *expand-list-case*:
$P(\textit{list-case}\ a\ f\ xs) = ((xs{=}[] \longrightarrow P\ a\ ) \wedge (\forall y\ ys.\ xs{=}y\#ys \longrightarrow P(f\ y\ ys)))$
by (*induct xs rule*: *list-induct*) *simp-all*

declare *def-list-rec-NilCons* [*OF map-def*, *simp*]

lemma *Abs-Rep-map*:
$(\bigwedge x.\ f(x) \in \textit{sexp}) \Longrightarrow$
$\textit{Abs-map}\ g\ (\textit{Rep-map}\ f\ xs) = \textit{map}\ (\lambda t.\ g(f(t)))\ xs$
apply (*induct xs rule*: *list-induct*)
apply (*simp-all add*: *Rep-map-type list-sexp* [*THEN subsetD*])
done

lemma *map-ident* [*simp*]: $\textit{map}(\%x.\ x)(xs) = xs$
by (*induct xs rule*: *list-induct*) *simp-all*

lemma *map-compose*: $\textit{map}(f\ o\ g)(xs) = \textit{map}\ f\ (\textit{map}\ g\ xs)$
apply (*simp add*: *o-def*)
apply (*induct xs rule*: *list-induct*)
apply *simp-all*

done

lemma *take-Suc1* [*simp*]: *take* [] (*Suc x*) = []
by *simp*

lemma *take-Suc2* [*simp*]: *take*(*a*#*xs*)(*Suc x*) = *a*#*take xs x*
by *simp*

lemma *take-Nil* [*simp*]: *take* [] *n* = []
by (*induct n*) *simp-all*

lemma *take-take-eq* [*simp*]: ∀ *n*. *take* (*take xs n*) *n* = *take xs n*
apply (*induct xs rule*: *list-induct*)
apply *simp-all*
apply (*rule allI*)
apply (*induct-tac n*)
apply *auto*
done

end

7 Arithmetic and boolean expressions

theory *ABexp*
imports *Main*
begin

datatype *'a aexp* =
  IF 'a bexp 'a aexp 'a aexp
 | *Sum 'a aexp 'a aexp*
 | *Diff 'a aexp 'a aexp*
 | *Var 'a*
 | *Num nat*
and *'a bexp* =
  Less 'a aexp 'a aexp
 | *And 'a bexp 'a bexp*
 | *Neg 'a bexp*

Evaluation of arithmetic and boolean expressions

primrec *evala* :: (*'a* ⇒ *nat*) ⇒ *'a aexp* ⇒ *nat*
 and *evalb* :: (*'a* ⇒ *nat*) ⇒ *'a bexp* ⇒ *bool*
where
 evala env (*IF b a1 a2*) = (*if evalb env b then evala env a1 else evala env a2*)
| *evala env* (*Sum a1 a2*) = *evala env a1* + *evala env a2*
| *evala env* (*Diff a1 a2*) = *evala env a1* − *evala env a2*

| *evala env* (*Var v*) = *env v*
| *evala env* (*Num n*) = *n*

| *evalb env* (*Less a1 a2*) = (*evala env a1* < *evala env a2*)
| *evalb env* (*And b1 b2*) = (*evalb env b1* ∧ *evalb env b2*)
| *evalb env* (*Neg b*) = (¬ *evalb env b*)

Substitution on arithmetic and boolean expressions

primrec *substa* :: ('*a* ⇒ '*b aexp*) ⇒ '*a aexp* ⇒ '*b aexp*
  and *substb* :: ('*a* ⇒ '*b aexp*) ⇒ '*a bexp* ⇒ '*b bexp*
where
  substa f (*IF b a1 a2*) = *IF* (*substb f b*) (*substa f a1*) (*substa f a2*)
| *substa f* (*Sum a1 a2*) = *Sum* (*substa f a1*) (*substa f a2*)
| *substa f* (*Diff a1 a2*) = *Diff* (*substa f a1*) (*substa f a2*)
| *substa f* (*Var v*) = *f v*
| *substa f* (*Num n*) = *Num n*

| *substb f* (*Less a1 a2*) = *Less* (*substa f a1*) (*substa f a2*)
| *substb f* (*And b1 b2*) = *And* (*substb f b1*) (*substb f b2*)
| *substb f* (*Neg b*) = *Neg* (*substb f b*)

lemma *subst1-aexp*:
  evala env (*substa* (*Var* (*v* := *a*′)) *a*) = *evala* (*env* (*v* := *evala env a*′)) *a*
and *subst1-bexp*:
  evalb env (*substb* (*Var* (*v* := *a*′)) *b*) = *evalb* (*env* (*v* := *evala env a*′)) *b*
    — one variable
  by (*induct a* **and** *b*) *simp-all*

lemma *subst-all-aexp*:
  evala env (*substa s a*) = *evala* (λ*x*. *evala env* (*s x*)) *a*
and *subst-all-bexp*:
  evalb env (*substb s b*) = *evalb* (λ*x*. *evala env* (*s x*)) *b*
  by (*induct a* **and** *b*) *auto*

end

8 Infinitely branching trees

theory *Infinitely-Branching-Tree*
imports *Main*
begin

datatype '*a tree* =
    Atom '*a*
  | *Branch nat* ⇒ '*a tree*

primrec *map-tree* :: ('*a* ⇒ '*b*) ⇒ '*a tree* ⇒ '*b tree*
  where

$\quad$ *map-tree f* (*Atom a*) = *Atom* (*f a*)
$\mid$ *map-tree f* (*Branch ts*) = *Branch* (λx. *map-tree f* (*ts x*))

lemma *tree-map-compose*: *map-tree g* (*map-tree f t*) = *map-tree* ($g \circ f$) *t*
by (*induct t*) *simp-all*

primrec *exists-tree* :: ($'a \Rightarrow$ *bool*) $\Rightarrow$ $'a$ *tree* $\Rightarrow$ *bool*
where
$\quad$ *exists-tree P* (*Atom a*) = *P a*
$\mid$ *exists-tree P* (*Branch ts*) = ($\exists x$. *exists-tree P* (*ts x*))

lemma *exists-map*:
($\bigwedge x$. *P x* $\Longrightarrow$ *Q* (*f x*)) $\Longrightarrow$
$\quad$ *exists-tree P ts* $\Longrightarrow$ *exists-tree Q* (*map-tree f ts*)
by (*induct ts*) *auto*

8.1 The Brouwer ordinals, as in ZF/Induct/Brouwer.thy.

datatype *brouwer* = *Zero* | *Succ brouwer* | *Lim nat* $\Rightarrow$ *brouwer*

Addition of ordinals

primrec *add* :: *brouwer* $\Rightarrow$ *brouwer* $\Rightarrow$ *brouwer*
where
$\quad$ *add i Zero* = *i*
$\mid$ *add i* (*Succ j*) = *Succ* (*add i j*)
$\mid$ *add i* (*Lim f*) = *Lim* (λn. *add i* (*f n*))

lemma *add-assoc*: *add* (*add i j*) *k* = *add i* (*add j k*)
by (*induct k*) *auto*

Multiplication of ordinals

primrec *mult* :: *brouwer* $\Rightarrow$ *brouwer* $\Rightarrow$ *brouwer*
where
$\quad$ *mult i Zero* = *Zero*
$\mid$ *mult i* (*Succ j*) = *add* (*mult i j*) *i*
$\mid$ *mult i* (*Lim f*) = *Lim* (λn. *mult i* (*f n*))

lemma *add-mult-distrib*: *mult i* (*add j k*) = *add* (*mult i j*) (*mult i k*)
by (*induct k*) (*auto simp add*: *add-assoc*)

lemma *mult-assoc*: *mult* (*mult i j*) *k* = *mult i* (*mult j k*)
by (*induct k*) (*auto simp add*: *add-mult-distrib*)

We could probably instantiate some axiomatic type classes and use the standard infix operators.

8.2 A WF Ordering for The Brouwer ordinals (Michael Compton)

To use the function package we need an ordering on the Brouwer ordinals. Start with a predecessor relation and form its transitive closure.

definition *brouwer-pred* :: (*brouwer* × *brouwer*) *set*
  where *brouwer-pred* = ($\bigcup i$. {(*m*, *n*). *n* = *Succ m* ∨ (∃*f*. *n* = *Lim f* ∧ *m* = *f i*)})

definition *brouwer-order* :: (*brouwer* × *brouwer*) *set*
  where *brouwer-order* = *brouwer-pred*$^+$

lemma *wf-brouwer-pred*: *wf brouwer-pred*
  unfolding *wf-def brouwer-pred-def*
  apply *clarify*
  apply (*induct-tac x*)
    apply *blast+*
  done

lemma *wf-brouwer-order*[*simp*]: *wf brouwer-order*
  unfolding *brouwer-order-def*
  by (*rule wf-trancl*[*OF wf-brouwer-pred*])

lemma [*simp*]: (*j*, *Succ j*) ∈ *brouwer-order*
  by (*auto simp add*: *brouwer-order-def brouwer-pred-def*)

lemma [*simp*]: (*f n*, *Lim f*) ∈ *brouwer-order*
  by (*auto simp add*: *brouwer-order-def brouwer-pred-def*)

Example of a general function

function *add2* :: *brouwer* ⇒ *brouwer* ⇒ *brouwer*
  where
    add2 i Zero = *i*
  | *add2 i* (*Succ j*) = *Succ* (*add2 i j*)
  | *add2 i* (*Lim f*) = *Lim* (λ*n*. *add2 i* (*f n*))
  by *pat-completeness auto*
termination
  by (*relation inv-image brouwer-order snd*) *auto*

lemma *add2-assoc*: *add2* (*add2 i j*) *k* = *add2 i* (*add2 j k*)
  by (*induct k*) *auto*

end

9 Ordinals

theory *Ordinals*
imports *Main*

begin

Some basic definitions of ordinal numbers. Draws an Agda development (in Martin-Löf type theory) by Peter Hancock (see http://www.dcs.ed.ac.uk/home/pgh/chat.html).

datatype *ordinal* =
  Zero
 | *Succ ordinal*
 | *Limit nat* ⇒ *ordinal*

primrec *pred* :: *ordinal* ⇒ *nat* ⇒ *ordinal option*
where
  pred Zero n = *None*
| *pred* (*Succ a*) *n* = *Some a*
| *pred* (*Limit f*) *n* = *Some* (*f n*)

abbreviation (*input*) *iter* :: ('*a* ⇒ '*a*) ⇒ *nat* ⇒ ('*a* ⇒ '*a*)
  where *iter f n* ≡ *f* ^^ *n*

definition *OpLim* :: (*nat* ⇒ (*ordinal* ⇒ *ordinal*)) ⇒ (*ordinal* ⇒ *ordinal*)
  where *OpLim F a* = *Limit* (λ*n*. *F n a*)

definition *OpItw* :: (*ordinal* ⇒ *ordinal*) ⇒ (*ordinal* ⇒ *ordinal*) (⨆)
  where ⨆*f* = *OpLim* (*iter f*)

primrec *cantor* :: *ordinal* ⇒ *ordinal* ⇒ *ordinal*
where
  cantor a Zero = *Succ a*
| *cantor a* (*Succ b*) = ⨆(λ*x*. *cantor x b*) *a*
| *cantor a* (*Limit f*) = *Limit* (λ*n*. *cantor a* (*f n*))

primrec *Nabla* :: (*ordinal* ⇒ *ordinal*) ⇒ (*ordinal* ⇒ *ordinal*) (∇)
where
  ∇*f Zero* = *f Zero*
| ∇*f* (*Succ a*) = *f* (*Succ* (∇*f a*))
| ∇*f* (*Limit h*) = *Limit* (λ*n*. ∇*f* (*h n*))

definition *deriv* :: (*ordinal* ⇒ *ordinal*) ⇒ (*ordinal* ⇒ *ordinal*)
  where *deriv f* = ∇(⨆*f*)

primrec *veblen* :: *ordinal* ⇒ *ordinal* ⇒ *ordinal*
where
  veblen Zero = ∇(*OpLim* (*iter* (*cantor Zero*)))
| *veblen* (*Succ a*) = ∇(*OpLim* (*iter* (*veblen a*)))
| *veblen* (*Limit f*) = ∇(*OpLim* (λ*n*. *veblen* (*f n*)))

definition *veb a* = *veblen a Zero*
definition ε_0 = *veb Zero*
definition Γ_0 = *Limit* (λ*n*. *iter veb n Zero*)

end

10 Sigma algebras

theory *Sigma-Algebra*
imports *Main*
begin

This is just a tiny example demonstrating the use of inductive definitions in classical mathematics. We define the least σ-algebra over a given set of sets.

inductive-set σ-*algebra* :: *'a set set* $\Rightarrow$ *'a set set* **for** A :: *'a set set*
where
  basic: $a \in \sigma$-*algebra* A **if** $a \in A$ **for** a
| *UNIV*: *UNIV* $\in \sigma$-*algebra* A
| *complement*: $-\ a \in \sigma$-*algebra* A **if** $a \in \sigma$-*algebra* A **for** a
| *Union*: $(\bigcup i.\ a\ i) \in \sigma$-*algebra* A **if** $\bigwedge i{::}nat.\ a\ i \in \sigma$-*algebra* A **for** a

The following basic facts are consequences of the closure properties of any σ-algebra, merely using the introduction rules, but no induction nor cases.

theorem *sigma-algebra-empty*: $\{\} \in \sigma$-*algebra* A
proof −
  have *UNIV* $\in \sigma$-*algebra* A **by** (*rule* σ-*algebra.UNIV*)
  then have $-$*UNIV* $\in \sigma$-*algebra* A **by** (*rule* σ-*algebra.complement*)
  also have $-$*UNIV* $= \{\}$ **by** *simp*
  finally show *?thesis* **.**
qed

theorem *sigma-algebra-Inter*:
  $(\bigwedge i{::}nat.\ a\ i \in \sigma\text{-}algebra\ A) \Longrightarrow (\bigcap i.\ a\ i) \in \sigma$-*algebra* A
proof −
  assume $\bigwedge i{::}nat.\ a\ i \in \sigma$-*algebra* A
  then have $\bigwedge i{::}nat.\ -(a\ i) \in \sigma$-*algebra* A **by** (*rule* σ-*algebra.complement*)
  then have $(\bigcup i.\ -(a\ i)) \in \sigma$-*algebra* A **by** (*rule* σ-*algebra.Union*)
  then have $-(\bigcup i.\ -(a\ i)) \in \sigma$-*algebra* A **by** (*rule* σ-*algebra.complement*)
  also have $-(\bigcup i.\ -(a\ i)) = (\bigcap i.\ a\ i)$ **by** *simp*
  finally show *?thesis* **.**
qed

end

11 Combinatory Logic example: the Church-Rosser Theorem

theory *Comb*
imports *Main*
begin

Combinator terms do not have free variables. Example taken from [**?**].

11.1 Definitions

Datatype definition of combinators S and K.

datatype *comb* = *K*
  | *S*
  | *Ap comb comb* (**infixl** · *90*)

Inductive definition of contractions, $\rightarrow^1$ and (multi-step) reductions, $\rightarrow$.

inductive *contract1* :: [*comb*,*comb*] ⇒ *bool* (**infixl** $\rightarrow^1$ *50*)
  where
    K: $K \cdot x \cdot y \rightarrow^1 x$
  | *S*: $S \cdot x \cdot y \cdot z \rightarrow^1 (x \cdot z) \cdot (y \cdot z)$
  | *Ap1*: $x \rightarrow^1 y \Longrightarrow x \cdot z \rightarrow^1 y \cdot z$
  | *Ap2*: $x \rightarrow^1 y \Longrightarrow z \cdot x \rightarrow^1 z \cdot y$

abbreviation
  contract :: [*comb*,*comb*] ⇒ *bool* (**infixl** → *50*) **where**
  contract ≡ *contract1***

Inductive definition of parallel contractions, $\Rrightarrow^1$ and (multi-step) parallel reductions, $\Rrightarrow$.

inductive *parcontract1* :: [*comb*,*comb*] ⇒ *bool* (**infixl** $\Rrightarrow^1$ *50*)
  where
    refl: $x \Rrightarrow^1 x$
  | *K*: $K \cdot x \cdot y \Rrightarrow^1 x$
  | *S*: $S \cdot x \cdot y \cdot z \Rrightarrow^1 (x \cdot z) \cdot (y \cdot z)$
  | *Ap*: $[\![x \Rrightarrow^1 y;\ z \Rrightarrow^1 w]\!] \Longrightarrow x \cdot z \Rrightarrow^1 y \cdot w$

abbreviation
  parcontract :: [*comb*,*comb*] ⇒ *bool* (**infixl** ⇛ *50*) **where**
  parcontract ≡ *parcontract1***

Misc definitions.

definition
  I :: *comb* **where**
  $I \equiv S \cdot K \cdot K$

definition
  diamond :: ([*comb*,*comb*] ⇒ *bool*) ⇒ *bool* **where**
    — confluence; Lambda/Commutation treats this more abstractly
  $diamond\ r \equiv \forall x\ y.\ r\ x\ y \longrightarrow$
    $(\forall y'.\ r\ x\ y' \longrightarrow$
      $(\exists z.\ r\ y\ z \wedge r\ y'\ z))$

11.2 Reflexive/Transitive closure preserves Church-Rosser property

Remark: So does the Transitive closure, with a similar proof

Strip lemma. The induction hypothesis covers all but the last diamond of the strip.

lemma *strip-lemma* [*rule-format*]:
  assumes *diamond r* **and** r: $r^{**}\ x\ y\ r\ x\ y'$
  shows $\exists\, z.\ r^{**}\ y'\ z \wedge r\ y\ z$
  using r
proof (*induction rule*: *rtranclp-induct*)
  case *base*
  then show *?case*
    by *blast*
next
  case (*step y z*)
  then show *?case*
    using ‹*diamond r*› **unfolding** *diamond-def*
    by (*metis rtranclp.rtrancl-into-rtrancl*)
qed

proposition *diamond-rtrancl*:
  assumes *diamond r*
  shows *diamond*(r^{**})
  unfolding *diamond-def*
proof (*intro strip*)
  fix $x\ y\ y'$
  assume $r^{**}\ x\ y\ r^{**}\ x\ y'$
  then show $\exists\, z.\ r^{**}\ y\ z \wedge r^{**}\ y'\ z$
  proof (*induction rule*: *rtranclp-induct*)
    case *base*
    then show *?case*
      by *blast*
  next
    case (*step y z*)
    then show *?case*
      by (*meson assms strip-lemma rtranclp.rtrancl-into-rtrancl*)
  qed
qed

11.3 Non-contraction results

Derive a case for each combinator constructor.

inductive-cases
  K-contractE [*elim*!]: $K \to^1 r$
  and *S-contractE* [*elim*!]: $S \to^1 r$
  and *Ap-contractE* [*elim*!]: $p \cdot q \to^1 r$

declare *contract1.K* [*intro*!] *contract1.S* [*intro*!]
declare *contract1.Ap1* [*intro*] *contract1.Ap2* [*intro*]

lemma *I-contract-E* [*iff*]: $\neg\ I \to^1 z$
  unfolding *I-def* **by** *blast*

lemma *K1-contractD* [*elim*!]: $K \cdot x \to^1 z \Longrightarrow (\exists\, x'.\ z = K \cdot x' \wedge x \to^1 x')$
  by *blast*

lemma *Ap-reduce1* [*intro*]: $x \to y \Longrightarrow x \cdot z \to y \cdot z$
  by (*induction rule*: *rtranclp-induct*; *blast intro*: *rtranclp-trans*)

lemma *Ap-reduce2* [*intro*]: $x \to y \Longrightarrow z \cdot x \to z \cdot y$
  by (*induction rule*: *rtranclp-induct*; *blast intro*: *rtranclp-trans*)

Counterexample to the diamond property for $x \to^1 y$

lemma *not-diamond-contract*: $\neg$ *diamond*(*contract1*)
  unfolding *diamond-def* **by** (*metis S-contractE contract1.K*)

11.4 Results about Parallel Contraction

Derive a case for each combinator constructor.

inductive-cases
    K-parcontractE [*elim*!]: $K \Rrightarrow^1 r$
  and *S-parcontractE* [*elim*!]: $S \Rrightarrow^1 r$
  and *Ap-parcontractE* [*elim*!]: $p \cdot q \Rrightarrow^1 r$

declare *parcontract1.intros* [*intro*]

11.5 Basic properties of parallel contraction

The rules below are not essential but make proofs much faster

lemma *K1-parcontractD* [*dest*!]: $K \cdot x \Rrightarrow^1 z \Longrightarrow (\exists\, x'.\ z = K \cdot x' \wedge x \Rrightarrow^1 x')$
  by *blast*

lemma *S1-parcontractD* [*dest*!]: $S \cdot x \Rrightarrow^1 z \Longrightarrow (\exists\, x'.\ z = S \cdot x' \wedge x \Rrightarrow^1 x')$
  by *blast*

lemma *S2-parcontractD* [*dest*!]: $S \cdot x \cdot y \Rrightarrow^1 z \Longrightarrow (\exists\, x'\ y'.\ z = S \cdot x' \cdot y' \wedge x \Rrightarrow^1 x'$
$\wedge\ y \Rrightarrow^1 y')$
  by *blast*

Church-Rosser property for parallel contraction

proposition *diamond-parcontract*: *diamond parcontract1*
proof −
  have $(\exists\, z.\ w \Rrightarrow^1 z \wedge y' \Rrightarrow^1 z)$ **if** $y \Rrightarrow^1 w$ $y \Rrightarrow^1 y'$ **for** $w\ y\ y'$
    using *that* **by** (*induction arbitrary*: y' *rule*: *parcontract1.induct*) *fast*+

then show *?thesis*
by (*auto simp*: *diamond-def*)
qed

11.6 Equivalence of $p \to q$ and $p \Rrightarrow q$.

lemma *contract-imp-parcontract*: $x \to^1 y \Longrightarrow x \Rrightarrow^1 y$
by (*induction rule*: *contract1.induct*; *blast*)

Reductions: simply throw together reflexivity, transitivity and the one-step reductions

proposition *reduce-I*: $I \cdot x \to x$
unfolding *I-def*
by (*meson contract1.K contract1.S r-into-rtranclp rtranclp.rtrancl-into-rtrancl*)

lemma *parcontract-imp-reduce*: $x \Rrightarrow^1 y \Longrightarrow x \to y$
proof (*induction rule*: *parcontract1.induct*)
case (*Ap x y z w*)
then show *?case*
by (*meson Ap-reduce1 Ap-reduce2 rtranclp-trans*)
qed *auto*

lemma *reduce-eq-parreduce*: $x \to y \longleftrightarrow x \Rrightarrow y$
by (*metis contract-imp-parcontract parcontract-imp-reduce predicate2I rtranclp-subset*)

theorem *diamond-reduce*: *diamond*(*contract*)
using *diamond-parcontract diamond-rtrancl reduce-eq-parreduce* **by** *presburger*

end

12 Meta-theory of propositional logic

theory *PropLog* **imports** *Main* **begin**

Datatype definition of propositional logic formulae and inductive definition of the propositional tautologies.

Inductive definition of propositional logic. Soundness and completeness w.r.t. truth-tables.

Prove: If $H \models p$ then $G \models p$ where $G \in Fin(H)$

12.1 The datatype of propositions

datatype *'a pl* =
false |
var 'a (#- [*1000*]) |
imp 'a pl 'a pl (**infixr** –> *90*)

12.2 The proof system

inductive *thms* :: [*'a pl set*, *'a pl*] => *bool* (**infixl** |− *50*)
  for *H* :: *'a pl set*
where
  H: *p*∈*H* ==> *H* |− *p*
| *K*: *H* |− *p*−>*q*−>*p*
| *S*: *H* |− (*p*−>*q*−>*r*) −> (*p*−>*q*) −> *p*−>*r*
| *DN*: *H* |− ((*p*−>*false*) −> *false*) −> *p*
| *MP*: [| *H* |− *p*−>*q*; *H* |− *p* |] ==> *H* |− *q*

12.3 The semantics

12.3.1 Semantics of propositional logic.

primrec *eval* :: [*'a set*, *'a pl*] => *bool* (-[[-]] [*100*,*0*] *100*)
where
  tt[[*false*]] = *False*
| *tt*[[#*v*]] = (*v* ∈ *tt*)
| *eval-imp*: *tt*[[*p*−>*q*]] = (*tt*[[*p*]] −−> *tt*[[*q*]])

A finite set of hypotheses from *t* and the *Var*s in *p*.

primrec *hyps* :: [*'a pl*, *'a set*] => *'a pl set*
where
  hyps false tt = {}
| *hyps* (#*v*) *tt* = {*if v* ∈ *tt then* #*v else* #*v*−>*false*}
| *hyps* (*p*−>*q*) *tt* = *hyps p tt Un hyps q tt*

12.3.2 Logical consequence

For every valuation, if all elements of *H* are true then so is *p*.

definition *sat* :: [*'a pl set*, *'a pl*] => *bool* (**infixl** |= *50*)
  where *H* |= *p* = (∀ *tt*. (∀ *q*∈*H*. *tt*[[*q*]]) −−> *tt*[[*p*]])

12.4 Proof theory of propositional logic

lemma *thms-mono*: *G*<=*H* ==> *thms*(*G*) <= *thms*(*H*)
apply (*rule predicate1I*)
apply (*erule thms.induct*)
apply (*auto intro*: *thms.intros*)
done

lemma *thms-I*: *H* |− *p*−>*p*
  — Called *I* for Identity Combinator, not for Introduction.
by (*best intro*: *thms.K thms.S thms.MP*)

12.4.1 Weakening, left and right

lemma *weaken-left*: [| *G* ⊆ *H*; *G*|−*p* |] ==> *H*|−*p*
  — Order of premises is convenient with *THEN*

by (*erule thms-mono* [*THEN predicate1D*])

lemma *weaken-left-insert*: G |− $p \Longrightarrow$ *insert a* G |− p
by (*rule weaken-left*) (*rule subset-insertI*)

lemma *weaken-left-Un1*: G |− $p \Longrightarrow G \cup B$ |− p
by (*rule weaken-left*) (*rule Un-upper1*)

lemma *weaken-left-Un2*: G |− $p \Longrightarrow A \cup G$ |− p
by (*rule weaken-left*) (*rule Un-upper2*)

lemma *weaken-right*: H |− q ==> H |− p−>q
by (*fast intro*: *thms.K thms.MP*)

12.4.2 The deduction theorem

theorem *deduction*: *insert* p H |− q ==> H |− p−>q
apply (*induct set*: *thms*)
apply (*fast intro*: *thms-I thms.H thms.K thms.S thms.DN*
thms.S [*THEN thms.MP*, *THEN thms.MP*] *weaken-right*)+
done

12.4.3 The cut rule

lemma *cut*: *insert* p H |− $q \Longrightarrow H$ |− $p \Longrightarrow H$ |− q
by (*rule thms.MP*) (*rule deduction*)

lemma *thms-falseE*: H |− *false* $\Longrightarrow H$ |− q
by (*rule thms.MP*, *rule thms.DN*) (*rule weaken-right*)

lemma *thms-notE*: H |− p −> *false* $\Longrightarrow H$ |− $p \Longrightarrow H$ |− q
by (*rule thms-falseE*) (*rule thms.MP*)

12.4.4 Soundness of the rules wrt truth-table semantics

theorem *soundness*: H |− p ==> H |= p
by (*induct set*: *thms*) (*auto simp*: *sat-def*)

12.5 Completeness

12.5.1 Towards the completeness proof

lemma *false-imp*: H |− p−>*false* ==> H |− p−>q
apply (*rule deduction*)
apply (*metis H insert-iff weaken-left-insert thms-notE*)
done

lemma *imp-false*:
[| H |− p; H |− q−>*false* |] ==> H |− (p−>q)−>*false*
apply (*rule deduction*)

apply (*metis H MP insert-iff weaken-left-insert*)
done

lemma *hyps-thms-if*: *hyps p tt* |− (*if tt*[[*p*]] *then p else p*−>*false*)
— Typical example of strengthening the induction statement.
apply *simp*
apply (*induct p*)
apply (*simp-all add*: *thms-I thms.H*)
apply (*blast intro*: *weaken-left-Un1 weaken-left-Un2 weaken-right*
imp-false false-imp)
done

lemma *sat-thms-p*: {} |= *p* ==> *hyps p tt* |− *p*
— Key lemma for completeness; yields a set of assumptions satisfying *p*
unfolding *sat-def*
by (*metis* (*full-types*) *empty-iff hyps-thms-if*)

For proving certain theorems in our new propositional logic.

declare *deduction* [*intro*!]
declare *thms.H* [*THEN thms.MP*, *intro*]

The excluded middle in the form of an elimination rule.

lemma *thms-excluded-middle*: *H* |− (*p*−>*q*) −> ((*p*−>*false*)−>*q*) −> *q*
apply (*rule deduction* [*THEN deduction*])
apply (*rule thms.DN* [*THEN thms.MP*], *best intro*: *H*)
done

lemma *thms-excluded-middle-rule*:
[| *insert p H* |− *q*; *insert* (*p*−>*false*) *H* |− *q* |] ==> *H* |− *q*
— Hard to prove directly because it requires cuts
by (*rule thms-excluded-middle* [*THEN thms.MP*, *THEN thms.MP*], *auto*)

12.6 Completeness – lemmas for reducing the set of assumptions

For the case *hyps p t* − *insert* #*v Y* |− *p* we also have *hyps p t* − {#*v*} ⊆ *hyps p* (*t* − {*v*}).

lemma *hyps-Diff*: *hyps p* (*t*−{*v*}) <= *insert* (#*v*−>*false*) ((*hyps p t*)−{#*v*})
by (*induct p*) *auto*

For the case *hyps p t* − *insert* (#*v* −> *Fls*) *Y* |− *p* we also have *hyps p t* − {#*v* −> *Fls*} ⊆ *hyps p* (*insert v t*).

lemma *hyps-insert*: *hyps p* (*insert v t*) <= *insert* (#*v*) (*hyps p t*−{#*v*−>*false*})
by (*induct p*) *auto*

Two lemmas for use with *weaken-left*

lemma *insert-Diff-same*: *B*−*C* <= *insert a* (*B*−*insert a C*)

by *fast*

lemma *insert-Diff-subset2*: *insert a* $(B-\{c\})$ $-$ D <= *insert a* $(B-$*insert c D*$)$
by *fast*

The set *hyps p t* is finite, and elements have the form $\#v$ or $\#v$ -> *Fls*.

lemma *hyps-finite*: *finite*(*hyps p t*)
by (*induct p*) *auto*

lemma *hyps-subset*: *hyps p t* <= (*UN v*. {$\#v$, $\#v$->*false*})
by (*induct p*) *auto*

lemma *Diff-weaken-left*: $A \subseteq C \Longrightarrow A - B$ |- $p \Longrightarrow C - B$ |- p
by (*rule Diff-mono* [*OF - subset-refl*, *THEN weaken-left*])

12.6.1 Completeness theorem

Induction on the finite set of assumptions *hyps p t0*. We may repeatedly subtract assumptions until none are left!

lemma *completeness-0-lemma*:
{} |= p ==> $\forall t$. *hyps p t* $-$ *hyps p t0* |- p
apply (*rule hyps-subset* [*THEN hyps-finite* [*THEN finite-subset-induct*]])
apply (*simp add*: *sat-thms-p*, *safe*)

Case *hyps p t*$-$*insert*($\#v, Y$) |- p

apply (*iprover intro*: *thms-excluded-middle-rule*
insert-Diff-same [*THEN weaken-left*]
insert-Diff-subset2 [*THEN weaken-left*]
hyps-Diff [*THEN Diff-weaken-left*])

Case *hyps p t*$-$*insert*($\#v$ -> *false*, Y) |- p

apply (*iprover intro*: *thms-excluded-middle-rule*
insert-Diff-same [*THEN weaken-left*]
insert-Diff-subset2 [*THEN weaken-left*]
hyps-insert [*THEN Diff-weaken-left*])
done

The base case for completeness

lemma *completeness-0*: {} |= p ==> {} |- p
by (*metis Diff-cancel completeness-0-lemma*)

A semantic analogue of the Deduction Theorem

lemma *sat-imp*: *insert p H* |= q ==> H |= p->q
by (*auto simp*: *sat-def*)

theorem *completeness*: *finite H* ==> H |= p ==> H |- p
apply (*induct arbitrary*: *p rule*: *finite-induct*)
apply (*blast intro*: *completeness-0*)

apply (*iprover intro*: *sat-imp thms.H insertI1 weaken-left-insert* [*THEN thms.MP*])
done

theorem *syntax-iff-semantics*: *finite H* ==> (*H* |− *p*) = (*H* |= *p*)
by (*blast intro*: *soundness completeness*)

end

13 Mutual Induction via Iteratived Inductive Definitions

theory *Com* **imports** *Main* **begin**

typedecl *loc*
type-synonym *state* = *loc* => *nat*

datatype
  exp = *N nat*
    | *X loc*
    | *Op nat* => *nat* => *nat exp exp*
    | *valOf com exp* (*VALOF* - *RESULTIS* - 60)
and
  com = *SKIP*
    | *Assign loc exp* (**infixl** := 60)
    | *Semi com com* (-;;- [60, 60] 60)
    | *Cond exp com com* (*IF* - *THEN* - *ELSE* - 60)
    | *While exp com* (*WHILE* - *DO* - 60)

13.1 Commands

Execution of commands

abbreviation (*input*)
  generic-rel (-/ −|[-]−> - [50,0,50] 50) **where**
  esig −|[*eval*]−> *ns* == (*esig*,*ns*) ∈ *eval*

Command execution. Natural numbers represent Booleans: 0=True, 1=False

inductive-set
  exec :: ((*exp*∗*state*) ∗ (*nat*∗*state*)) *set* => ((*com*∗*state*)∗*state*)*set*
  and *exec-rel* :: *com* ∗ *state* => ((*exp*∗*state*) ∗ (*nat*∗*state*)) *set* => *state* => *bool*
    (-/ −[-]−> - [50,0,50] 50)
  for *eval* :: ((*exp*∗*state*) ∗ (*nat*∗*state*)) *set*
  where
    csig −[*eval*]−> *s* == (*csig*,*s*) ∈ *exec eval*

  | *Skip*: (*SKIP*,*s*) −[*eval*]−> *s*

  | *Assign*: (*e*,*s*) −|[*eval*]−> (*v*,*s*′) ==> (*x* := *e*, *s*) −[*eval*]−> *s*′(*x*:=*v*)

| *Semi*: [| (*c0*,*s*) −[*eval*]−> *s2*; (*c1*,*s2*) −[*eval*]−> *s1* |]
==> (*c0* ;; *c1*, *s*) −[*eval*]−> *s1*

| *IfTrue*: [| (*e*,*s*) −|[*eval*]−> (*0*,*s'*); (*c0*,*s'*) −[*eval*]−> *s1* |]
==> (*IF e THEN c0 ELSE c1*, *s*) −[*eval*]−> *s1*

| *IfFalse*: [| (*e*,*s*) −|[*eval*]−> (*Suc 0*, *s'*); (*c1*,*s'*) −[*eval*]−> *s1* |]
==> (*IF e THEN c0 ELSE c1*, *s*) −[*eval*]−> *s1*

| *WhileFalse*: (*e*,*s*) −|[*eval*]−> (*Suc 0*, *s1*)
==> (*WHILE e DO c*, *s*) −[*eval*]−> *s1*

| *WhileTrue*: [| (*e*,*s*) −|[*eval*]−> (*0*,*s1*);
(*c*,*s1*) −[*eval*]−> *s2*; (*WHILE e DO c*, *s2*) −[*eval*]−> *s3* |]
==> (*WHILE e DO c*, *s*) −[*eval*]−> *s3*

declare *exec.intros* [*intro*]

inductive-cases
[*elim*!]: (*SKIP*,*s*) −[*eval*]−> *t*
and [*elim*!]: (*x*:=*a*,*s*) −[*eval*]−> *t*
and [*elim*!]: (*c1*;;*c2*, *s*) −[*eval*]−> *t*
and [*elim*!]: (*IF e THEN c1 ELSE c2*, *s*) −[*eval*]−> *t*
and *exec-WHILE-case*: (*WHILE b DO c*,*s*) −[*eval*]−> *t*

Justifies using "exec" in the inductive definition of "eval"

lemma *exec-mono*: *A*<=*B* ==> *exec*(*A*) <= *exec*(*B*)
apply (*rule subsetI*)
apply (*simp add*: *split-paired-all*)
apply (*erule exec.induct*)
apply *blast*+
done

lemma [*pred-set-conv*]:
((λ*x x' y y'*. ((*x*, *x'*), (*y*, *y'*)) ∈ *R*) <= (λ*x x' y y'*. ((*x*, *x'*), (*y*, *y'*)) ∈ *S*)) = (*R* <= *S*)
unfolding *subset-eq*
by (*auto simp add*: *le-fun-def*)

lemma [*pred-set-conv*]:
((λ*x x' y*. ((*x*, *x'*), *y*) ∈ *R*) <= (λ*x x' y*. ((*x*, *x'*), *y*) ∈ *S*)) = (*R* <= *S*)
unfolding *subset-eq*
by (*auto simp add*: *le-fun-def*)

Command execution is functional (deterministic) provided evaluation is

theorem *single-valued-exec*: *single-valued ev* ==> *single-valued*(*exec ev*)
apply (*simp add*: *single-valued-def*)

apply (*intro allI*)
apply (*rule impI*)
apply (*erule exec.induct*)
apply (*blast elim*: *exec-WHILE-case*)+
done

13.2 Expressions

Evaluation of arithmetic expressions

inductive-set
  eval :: ((*exp*∗*state*) ∗ (*nat*∗*state*)) *set*
  and *eval-rel* :: [*exp*∗*state*,*nat*∗*state*] => *bool* (**infixl** −|−> *50*)
  where
    esig −|−> *ns* == (*esig*, *ns*) ∈ *eval*

  | *N* [*intro*!]: (*N*(*n*),*s*) −|−> (*n*,*s*)

  | *X* [*intro*!]: (*X*(*x*),*s*) −|−> (*s*(*x*),*s*)

  | *Op* [*intro*]: [| (*e0*,*s*) −|−> (*n0*,*s0*); (*e1*,*s0*) −|−> (*n1*,*s1*) |]
        ==> (*Op f e0 e1*, *s*) −|−> (*f n0 n1*, *s1*)

  | *valOf* [*intro*]: [| (*c*,*s*) −[*eval*]−> *s0*; (*e*,*s0*) −|−> (*n*,*s1*) |]
        ==> (*VALOF c RESULTIS e*, *s*) −|−> (*n*, *s1*)

  monos *exec-mono*

inductive-cases
    [*elim*!]: (*N*(*n*),*sigma*) −|−> (*n*′,*s*′)
  and [*elim*!]: (*X*(*x*),*sigma*) −|−> (*n*,*s*′)
  and [*elim*!]: (*Op f a1 a2*,*sigma*) −|−> (*n*,*s*′)
  and [*elim*!]: (*VALOF c RESULTIS e*, *s*) −|−> (*n*, *s1*)

lemma *var-assign-eval* [*intro*!]: (*X x*, *s*(*x*:=*n*)) −|−> (*n*, *s*(*x*:=*n*))
  by (*rule fun-upd-same* [*THEN subst*]) *fast*

Make the induction rule look nicer – though *eta-contract* makes the new version look worse than it is...

lemma *split-lemma*: {((*e*,*s*),(*n*,*s*′)). *P e s n s*′} = *Collect* (*case-prod* (%*v*. *case-prod* (*case-prod P v*)))
  by *auto*

New induction rule. Note the form of the VALOF induction hypothesis

lemma *eval-induct*
  [*case-names N X Op valOf*, *consumes 1*, *induct set*: *eval*]:
  [| (*e*,*s*) −|−> (*n*,*s*′);

```
    !!n s. P (N n) s n s;
    !!s x. P (X x) s (s x) s;
    !!e0 e1 f n0 n1 s s0 s1.
      [| (e0,s) -|-> (n0,s0); P e0 s n0 s0;
         (e1,s0) -|-> (n1,s1); P e1 s0 n1 s1
      |] ==> P (Op f e0 e1) s (f n0 n1) s1;
    !!c e n s s0 s1.
      [| (c,s) -[eval Int {((e,s),(n,s')). P e s n s'}]-> s0;
         (c,s) -[eval]-> s0;
         (e,s0) -|-> (n,s1); P e s0 n s1 |]
      ==> P (VALOF c RESULTIS e) s n s1
  |] ==> P e s n s'
apply (induct set: eval)
apply blast
apply blast
apply blast
apply (frule Int-lower1 [THEN exec-mono, THEN subsetD])
apply (auto simp add: split-lemma)
done
```

Lemma for *Function-eval*. The major premise is that (*c*,*s*) executes to *s1* using eval restricted to its functional part. Note that the execution (*c*,*s*) −[*eval*]−> *s2* can use unrestricted *eval*! The reason is that the execution (*c*,*s*) −[*eval Int* {...}]−> *s1* assures us that execution is functional on the argument (*c*,*s*).

```
lemma com-Unique:
 (c,s) -[eval Int {((e,s),(n,t)). ∀ nt'. (e,s) -|-> nt' --> (n,t)=nt'}]-> s1
  ==> ∀ s2. (c,s) -[eval]-> s2 --> s2=s1
apply (induct set: exec)
     apply simp-all
     apply blast
    apply force
   apply blast
  apply blast
 apply blast
 apply (blast elim: exec-WHILE-case)
apply (erule-tac V = (c,s2) -[ev]-> s3 for c ev in thin-rl)
apply clarify
apply (erule exec-WHILE-case, blast+)
done
```

Expression evaluation is functional, or deterministic

```
theorem single-valued-eval: single-valued eval
apply (unfold single-valued-def)
apply (intro allI, rule impI)
apply (simp (no-asm-simp) only: split-tupled-all)
apply (erule eval-induct)
apply (drule-tac [4] com-Unique)
apply (simp-all (no-asm-use))
```

apply *blast+*
done

lemma *eval-N-E* [*dest*!]: (*N n*, *s*) −|−> (*v*, *s'*) ==> (*v* = *n* & *s'* = *s*)
by (*induct e* == *N n s v s' set*: *eval*) *simp-all*

This theorem says that "WHILE TRUE DO c" cannot terminate

lemma *while-true-E*:
(*c'*, *s*) −[*eval*]−> *t* ==> *c'* = *WHILE* (*N 0*) *DO c* ==> *False*
by (*induct set*: *exec*) *auto*

13.3 Equivalence of IF e THEN c;;(WHILE e DO c) ELSE SKIP and WHILE e DO c

lemma *while-if1*:
(*c'*,*s*) −[*eval*]−> *t*
==> *c'* = *WHILE e DO c* ==>
(*IF e THEN c*;;*c' ELSE SKIP*, *s*) −[*eval*]−> *t*
by (*induct set*: *exec*) *auto*

lemma *while-if2*:
(*c'*,*s*) −[*eval*]−> *t*
==> *c'* = *IF e THEN c*;;(*WHILE e DO c*) *ELSE SKIP* ==>
(*WHILE e DO c*, *s*) −[*eval*]−> *t*
by (*induct set*: *exec*) *auto*

theorem *while-if*:
((*IF e THEN c*;;(*WHILE e DO c*) *ELSE SKIP*, *s*) −[*eval*]−> *t*) =
((*WHILE e DO c*, *s*) −[*eval*]−> *t*)
by (*blast intro*: *while-if1 while-if2*)

13.4 Equivalence of (IF e THEN c1 ELSE c2);;c and IF e THEN (c1;;c) ELSE (c2;;c)

lemma *if-semi1*:
(*c'*,*s*) −[*eval*]−> *t*
==> *c'* = (*IF e THEN c1 ELSE c2*);;*c* ==>
(*IF e THEN* (*c1*;;*c*) *ELSE* (*c2*;;*c*), *s*) −[*eval*]−> *t*
by (*induct set*: *exec*) *auto*

lemma *if-semi2*:
(*c'*,*s*) −[*eval*]−> *t*
==> *c'* = *IF e THEN* (*c1*;;*c*) *ELSE* (*c2*;;*c*) ==>
((*IF e THEN c1 ELSE c2*);;*c*, *s*) −[*eval*]−> *t*
by (*induct set*: *exec*) *auto*

theorem *if-semi*: (((*IF e THEN c1 ELSE c2*);;*c*, *s*) −[*eval*]−> *t*) =
((*IF e THEN* (*c1*;;*c*) *ELSE* (*c2*;;*c*), *s*) −[*eval*]−> *t*)

by (*blast intro*: *if-semi1 if-semi2*)

13.5 Equivalence of VALOF c1 RESULTIS (VALOF c2 RESULTIS e) and VALOF c1;;c2 RESULTIS e

lemma *valof-valof1*:
(*e'*,*s*) −|−> (*v*,*s'*)
==> *e'* = *VALOF c1 RESULTIS* (*VALOF c2 RESULTIS e*) ==>
(*VALOF c1*;;*c2 RESULTIS e*, *s*) −|−> (*v*,*s'*)
by (*induct set*: *eval*) *auto*

lemma *valof-valof2*:
(*e'*,*s*) −|−> (*v*,*s'*)
==> *e'* = *VALOF c1*;;*c2 RESULTIS e* ==>
(*VALOF c1 RESULTIS* (*VALOF c2 RESULTIS e*), *s*) −|−> (*v*,*s'*)
by (*induct set*: *eval*) *auto*

theorem *valof-valof*:
((*VALOF c1 RESULTIS* (*VALOF c2 RESULTIS e*), *s*) −|−> (*v*,*s'*)) =
((*VALOF c1*;;*c2 RESULTIS e*, *s*) −|−> (*v*,*s'*))
by (*blast intro*: *valof-valof1 valof-valof2*)

13.6 Equivalence of VALOF SKIP RESULTIS e and e

lemma *valof-skip1*:
(*e'*,*s*) −|−> (*v*,*s'*)
==> *e'* = *VALOF SKIP RESULTIS e* ==>
(*e*, *s*) −|−> (*v*,*s'*)
by (*induct set*: *eval*) *auto*

lemma *valof-skip2*:
(*e*,*s*) −|−> (*v*,*s'*) ==> (*VALOF SKIP RESULTIS e*, *s*) −|−> (*v*,*s'*)
by *blast*

theorem *valof-skip*:
((*VALOF SKIP RESULTIS e*, *s*) −|−> (*v*,*s'*)) = ((*e*, *s*) −|−> (*v*,*s'*))
by (*blast intro*: *valof-skip1 valof-skip2*)

13.7 Equivalence of VALOF x:=e RESULTIS x and e

lemma *valof-assign1*:
(*e'*,*s*) −|−> (*v*,*s''*)
==> *e'* = *VALOF x*:=*e RESULTIS X x* ==>
(∃ *s'*. (*e*, *s*) −|−> (*v*,*s'*) & (*s''* = *s'*(*x*:=*v*)))
by (*induct set*: *eval*) (*simp-all del*: *fun-upd-apply*, *clarify*, *auto*)

lemma *valof-assign2*:
(*e*,*s*) −|−> (*v*,*s'*) ==> (*VALOF x*:=*e RESULTIS X x*, *s*) −|−> (*v*,*s'*(*x*:=*v*))
by *blast*

end